



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCMD XCKD XCKT XCKP
Associated body	ZCP39 ZCMD29C12 ZCMD37L1 ZCMD41L2 ZCMD25L5 ZCT26N12 ZCT21P16 ZCD29 ZCT21N12 ZCT28G11 ZCMD21L2 ZCMD39L5 ZCT26P16 ZCMD39L2 ZCMD37L2 ZCP27 ZCP21M12 ZCD31 ZCMD61C12 ZCD26 ZCD21M12 ZCT26G11 ZCMD29L2 ZCMD25L2 ZCMD21C12 ZCMD21M12

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

ZCP35
 ZCMD21L1
 ZCT28N12
 ZCD35
 ZCMD29L1
 ZCD25
 ZCMD81L2
 ZCT27P16
 ZCMD69C12
 ZCD29M12
 ZCMD25L1
 ZCT27G11
 ZCD37
 ZCD21
 ZCMD21L08U78
 ZCT27N12
 ZCP26
 ZCMD81L5
 ZCP29
 ZCP29M12
 ZCMD41L1
 ZCT21G11
 ZCP25
 ZCMD41L5
 ZCT25N12
 ZCMD29L5
 ZCMD39L1
 ZCD28
 ZCT25G11
 ZCD27
 ZCD39
 ZCMD37L5
 ZCT25P16
 ZCP21
 ZCP31
 ZCMD81L1
 ZCMD21L08R12
 ZCMD61M12
 ZCP28
 ZCMD21L5
 ZCP37
 ZCT28P16

Movement of operating head	Linear
Type of operator	Side roller plunger spring return metal (with horizontal roller)
Type of approach	Lateral approach, 2 directions

Complementary

Switch actuation	By 30° cam
Positive opening	Without

Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.13 lb(US) (0.057 kg)
Package 1 Height	0.180 dm
Package 1 width	0.500 dm
Package 1 Length	0.320 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------