



Representative

Catalog Number: **RG12S1442LD9**
Product ID: 7TBA133590R1435
UPC Number: 62461628050
Status: Active

Battery Unit, Battery Type: lead-calcium, Voltage DC: 12V, Battery Wattage: 144W, self-powered, Colour: factory white, 120/347VAC, two lamps, Lamp Type: MR16 LED, Lamp Voltage: 12V, Lamp Wattage: 5W, Head Style: standard, Battery Run Time (Minimum): 30 minutes

10-year life expectancy, maintenance-free emergency lighting units. 6, 12 and 24 Volts

- Removable front panel on cabinet provides easy access and allows the unit to be mounted at ceiling height
- Solid-state pulse-type charger, current-limited, temperaturecompensated, short-circuit proof and reverse-polarity protected
- Unit comes standard with electronic lockout and brownout circuits
- Sealed dust-proof transfer relay, test switch and LED indicator lights
- "Long-life, maintenance-free Lead-Acid battery";

North American Specifications (UNSPSC)

| | |
|-----------------|--|
| UNSPSC | 39111709 Emergency light unit |
| IGCC | 3940 Emergency light unit |
| Brand Name | Lumacell |
| Type | Battery Unit |
| Application | Institutional, Industrial, Commercial, Hospitality |
| Standard | CSA |
| Wattage | 144W |
| Voltage Rating | 120/347VAC, 12VDC |
| Battery | Lead-calcium |
| Battery Runtime | 30 minutes |
| Lamp Type | MR16 LED |
| Number Of Lamps | 2 |
| Size | 16-1/2 Inches Height x 13-1/4 Inches Width |
| Material | Cabinet: Steel |
| Mounting | Wall |
| Color | Factory white |
| Lamp Wattage | 5W |

European Specifications (ETIM)

| | |
|------------------|------------------------------|
| ETIM | EC001957 Emergency luminaire |
| Lamp type | LED exchangeable |
| Lamp power | 5W |
| Material housing | Steel |
| Colour housing | White |
| Battery quality | Lead |
| Voltage type | AC/DC |
| Nominal voltage | 120-347V |
| Width | 337mm |

Packaging

| | |
|---------------------------|----------------|
| Outer Quantity | 1 |
| Outer Dimensions (inches) | 4.875x14x17.75 |
| Weight Uom | 17 lbs. Each |

Documents / Support Tools

| | |
|-------------------------|----------------------|
| Technical Data Sheet CA | Available on Website |
|-------------------------|----------------------|