


Product Datasheet

Characteristic

XCSE5333

metal safety switch XCSE - 1NC+2NO-
slow break-2entries tapped 1/2" NPT-
110/120V



Main

range of product	Preventa Safety detection
product or component type	safety switch
component name	XCSE
design	rectangular
material	metal
head type	key operated turret head
contacts type and composition	1 NC + 2 NO
contacts operation	slow-break, break before make
solenoid contacts type and composition	1 NC + 1 NO (slow-break, simultaneous)
cable entry	2 entries tapped 1/2" NPT
electromagnet interlocking	locking on de-energisation and unlocking on energisation of solenoid
[Us] rated supply voltage	110/120 V (- 20...10 %)
electrical connection	terminal, 1 x 0.5...2 x 1.5 mm ² with or without cable end
number of poles	3
locking options description	with interlocking, locking by solenoid
local signalling	2 LEDs green or orange (guard open/guard closed and locked)
signalling circuit voltage	110/240 V (voltage limits: 95...264 V)

Complementary

positive opening	with NC contact
supply voltage type	AC/DC
supply frequency	50/60 Hz
load factor	1
power consumption in VA	10 VA (inrush) 10 VA (sealed)
signalling circuit type	AC
signalling circuit consumption	7 mA
mechanical durability	>= 1000000 cycles
minimum actuation speed	0.03 ft/s (0.01 m/s)
maximum actuation speed	1.64 ft/s (0.5 m/s)

[Ie] rated operational current	0.55 A at 125 V utilisation category DC-13, Q300 conforming to EN/IEC 60947-5-1 0.27 A at 250 V utilisation category DC-13, Q300 conforming to EN/IEC 60947-5-1 3 A at 120 V utilisation category AC-15, B300 conforming to EN/IEC 60947-5-1 1.5 A at 240 V utilisation category AC-15, B300 conforming to EN/IEC 60947-5-1
[Ithe] conventional enclosed thermal current	6 A
[Ui] rated insulation voltage	250 V for signalling circuit conforming to EN/IEC 60947-1
[Uimp] rated impulse withstand voltage	6 kV conforming to EN/IEC 60947-5-1
protection type	overvoltage protection signalling circuit
short circuit protection	10 A cartridge fuse type gG (gl)
actutr forcible withdrawal rtc	2000 N
actuator force for extraction	>= 20 N
operating rate	10 cyc/mn for maximum durability
safety level	can reach category 4 with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1 can reach PL = e with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1 can reach SIL 3 with the appropriate monitoring system and correctly wired conforming to EN/IEC 61508
safety reliability data	B10d = 5000000 (value given for a life time of 20 years limited by mechanical or contact wear)
body material	zamak
head material	zamak
depth	1.73 in (44 mm)
height	5.75 in (146 mm)
width	3.86 in (98 mm)
product weight	2.51 lb(US) (1.14 kg)

Environment

standards	EN 1088/ISO 14119 EN/IEC 60204-1 EN/IEC 60947-5-1 EN/ISO 12100 UL 508 CSA C22.2 No 14
product certifications	CSA UL
protective treatment	TC
ambient air temperature for operation	-25...40 °C
ambient air temperature for storage	-40...158 °F (-40...70 °C)
vibration resistance	5 gn (f = 10...500 Hz) conforming to IEC 60068-2-6
shock resistance	10 gn 11 ms conforming to IEC 60068-2-27
class of protection against electric shock	class I conforming to EN/IEC 60536
IP degree of protection	IP67 conforming to EN/IEC 60529 and EN/IEC 60947-5-1

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1150 -
REACH	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------