NSYMF108
Microperforated mounting plate H1000xW800 w/holes diam 3,6mm on 12,5mm pitch

Green Premium™ Product

Main

Range	Spacial
Accessory / separate part category	Mounting accessory
Product or Component Type	Mounting plate
Device Application	Multi-purpose
Enclosure nominal dimensions	- H: 31.50 in (800 mm) W: 39.37 in (1000 mm) - H: 39.37 in (1000 mm) W: 31.50 in (800 mm)
Mounting Location	Step slide Direct fixing on backstuds
Mounting plate description	Microperforated
Range compatibility	Spacial Spacial S3D Spacial Spacial CRN Spacial Spacial S3X Thalassa Thalassa PLM
Quantity per Set	Set of 1
Material	Galvanised steel

Complementary

Fixing mode	Screwed on backstuds M8 By fixing element
Permanent permissible load	330.69 lb(US) (150 kg)
Height	37.99 in (965 mm)
Width	29.53 in (750 mm)
Depth	4.92 in (125 mm)
Thickness	0.10 in (2.5 mm)
Net Weight	28.40 lb(US) (12.88 kg)
Variant particularity	Installation in enclosures with inverted dimensions

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480183003
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.12 in (0.3 cm)
Package 1 Width	29.72 in (75.5 cm)
Package 1 Length	37.99 in (96.5 cm)
Package 1 Weight	29.26 lb(US) (13.27 kg)
Unit Type of Package 2	PAM
Number of Units in Package 2	40
Package 2 Height	12.60 in (32.0 cm)
Package 2 Width	39.37 in (100.0 cm)

Package 2 Length	47.24 in (120.0 cm)
Package 2 Weight	1221.36 lb(US) (554.0 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months

Life Is On | Schneider Electric