# **Product Datasheet**

### Characteristic

# NSYCRNG128300

Spacial CRNG plain door w/o mount.plate. H1200xW800xD300 IP66 IK10 RAL7035







#### Main

range	Spacial
product name	Spacial CRNG
device application	Multi-purpose
product or component type	Compact enclosure
enclosure nominal height	47.24 in (1200 mm)
enclosure nominal width	31.5 in (800 mm)
enclosure nominal depth	11.81 in (300 mm)
installation accessory type	Wall-mounting
device composition	Lock 1 Door 1 Body 1 Cable gland plate 2 bottom
door type	Plain
mounting plate description	Without mounting plate

## Complementary

· · · · · · · · · · · · · · · · · · ·		
variant particularity	Single piece body	
number of doors	1 front face	
door opening side	Reversible 120 °	
lock type	3 points lock, 5 mm double-bar	
type of gland plate	Standard	
accessibility for operation	Front	
removable parts	Door by hinges Cable gland plate by screws	
material	Steel body	
surface finish	Epoxy-polyester powder	
colour	Grey RAL 7035	
standards	IEC 62208	
product certifications	CUL UL	
product weight	44.2 kg	

### Environment

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0810 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations