# VW3M5103R200

power cable - between servomotor BSH and servodrive - 4 x 4 mmÂ<sup>2</sup> + 2 x 1 mmÂ<sup>2</sup> -20m





#### Main

Product or Component Type	Power cable
Accessory / separate part type	Preassembled power cordset
Accessory / separate part category	Connection accessory
Product compatibility	Servo motor BMH, 1 7.48 in (190 mm))E IEC 60204-1 Servo motor BMH, 3 8.07 in (205 mm))E IEC 60204-1 Servo motor BSH, 2 5.51 in (140 mm)) Servo motor BSH, 3 5.51 in (140 mm)) Servo motor BSH, 4 5.51 in (140 mm))
Accessory / separate part destination	Between servo motor and servo drive
Range Compatibility	Lexium 05 Lexium 15 Lexium 32
Cable length	65.62 ft (20 m)
Cable composition	4 x 4 mm² + 2 x 1 mm²

#### Complementary

Electrical connection	Free end servo drive side Connector - industrial M40 servo motor side
Net Weight	17.84 lb(US) (8.09 kg)

#### Ordering and shipping details

<u> </u>	
Category	18263-LEXIUM 32 ACCESSORIES
Discount Schedule	PC51
GTIN	3389119207430
Returnability	No
Country of origin	CZ

### **Packing Units**

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.54 in (9.0 cm)
Package 1 Width	19.69 in (50.0 cm)
Package 1 Length	19.69 in (50.0 cm)
Package 1 Weight	19.58 lb(US) (8.88 kg)

## Offer Sustainability

Contractual warranty

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information
PVC free	Yes

18 months