Rittal - The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 8017.581

Date: May 1, 2017



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Wallmounted enclosure - WM 8017.581 - WM363612NC

: 01.05.2017 build on www.rittal.com/ca-en



Product	descri	ption
1 I O G G C C	acson	Puvii

Material: Door: Carbon steel, all-round foamed-in PU seal

Housing: Carbon steel

Surface finish: Housing and door: Dipcoat primed, powder-coated on the outside, textured paint

Mounting plate: Zinc-plated

Color: RAL 7035

Protection category IP to IEC 60 529:

IP 66

Protection category

NEMA:

NEMA 4

Supply includes: Housing with door(s)

Left hand hinge Mounting plate

Rear wall mounting holes

Quarter turn latch with slotted head insert

Product features

Dimensions: Height: 900 mm (35 ")

Width: 900 mm (35 ") Depth: 300 mm (12 ")

Material thickness:: Housing: 2 mm (0.08 ")

Door: 2 mm (0.08 ")

Mounting plate: 2.5 mm (0.1 ")

Mounting plate: Height: 870 mm (34 ")

Width: 840 mm (33 ")

© Rittal 2017

Packaging unit:	1 pc(s).
Weight/packaging unit:	64 kg (141.1 lb.)
Approvals	
Approvals:	UL

2017 © Rittal Corporation

© Rittal 2017 2