Product data sheet

Specifications





Advanced box, Harmony P6, Intel Core i5-8365UE, 4 cores, 8 threads, for configured products

HMIP65BCTO

Main

Range of Product	Harmony P6	
Product or Component Type	Modular box PC	
Device short name	HMP65	
Operating system	Windows 10 IoT Enterprise 64 bitmulti-language	
Video controller type	Intel UHD Graphics 620	

Complementary

	5
Range compatibility	FP5000 PS6000 FP6000
Number of slots	2 slot(s) for optional interfaceslot-IN
Inrush current	30 A
Type of cooling	Fanless Fan with HDD
Width	11.4 in (290 mm)
Height	7.7 in (195 mm)
Net Weight	7.7 lb(US) (3.5 kg)

Environment

Product certifications	CE CULus CSA UL 61010-2-201 RCM UKCA DNV (DC model without HDD/fan/ EtherCAT card/22" wide display with expansion slot) ATEX zone 22 dust ATEX zone 22 dust ATEX zone 2 CULus Class 1 Division 2 (without DIO option) IECEx zone 2 (DC model, front USB cover must be locked with screw)

NEMA degree of protection

NEMA 4X/13

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Ambient air temperature for operation	32131 °F (055 °C) wall mounting without HDD) side EN/IEC 60068-2-2 32131 °F (055 °C) book mounting without HDD) side 32122 °F (050 °C) flat mounting without HDD) top 32122 °F (050 °C) book mounting without HDD) top 32113 °F (045 °C) wall mounting with HDD and fan kit) side 32113 °F (045 °C) flat mounting with HDD and fan kit) side 32113 °F (045 °C) flat mounting with HDD and fan kit) side 32113 °F (045 °C) book mounting with HDD and fan kit) top 32113 °F (045 °C) book mounting with HDD and fan kit) top 32113 °F (045 °C) panel without HDD) landscape 32122 °F (050 °C) panel without HDD) portrait 32113 °F (045 °C) panel with HDD and fan kit) landscape 32113 °F (045 °C) panel with HDD and fan kit) landscape	
Pollution degree	2	
Operating altitude	6561.68 ft (2000 m)	
Shock resistance	147 m/s ² X, Y, Z directions for 3 times IEC 61131-2	

Ordering and shipping details GTIN 3606481977328

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	6.1 in (15.5 cm)	
Package 1 Width	11.02 in (28.0 cm)	
Package 1 Length	15.4 in (39.0 cm)	
Package 1 Weight	9.9 lb(US) (4.5 kg)	

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Rohs Exemption Information

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Dimensions Drawings

Dimensions

External Dimensions



(A) : Front (B) : Left

(C) : Bottom

External Dimensions with PCI/PCIe Slots and FAN kit



(A) : Front

(B) : Left

(C) : Bottom

Dimensions with Book Mount Adapter (Top)



(A) : Front

(B) : Bottom

Dimensions with Book Mount Adapter (Side)





(B) : Right (C) : Bottom