



Main

Product or Component Type	Holding brake controller
Range Compatibility	Lexium 28 Lexium 05
Mounting support	2.17 in (55 mm) symmetrical DIN rail
Power supply voltage	24 V
Supply circuit type	DC

Complementary

Power supply voltage limits	19.2...30 V
Input current	0.5 A + brake nominal current
Maximum power consumption	50 W
Output voltage	17...19 V DC 23...25 V DC before power reduction
Maximum braking current	1.6 A
Time before voltage reduction	1000 ms
Net Weight	1.32 lb(US) (0.6 kg)

Environment

IP Degree of Protection	IP20
-------------------------	------

Ordering and shipping details

Category	18305-MOTION CONTROL CONNECTORS & ACCESS
Discount Schedule	PC51
GTIN	3389119207829
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.15 in (8.0 cm)
Package 1 Width	6.89 in (17.5 cm)
Package 1 Length	9.45 in (24.0 cm)
Package 1 Weight	10.19 oz (289.0 g)
Unit Type of Package 2	S06
Number of Units in Package 2	48
Package 2 Height	28.94 in (73.5 cm)
Package 2 Width	23.62 in (60.0 cm)
Package 2 Length	31.50 in (80.0 cm)
Package 2 Weight	59.24 lb(US) (26.872 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------