



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCKT XCMD XCKP XCKD
Associated body	ZCP29 ZCD39 ZCP26 ZCMD69C12 ZCD21M12 ZCMD29L2 ZCMD39L5 ZCD27 ZCMD29C12 ZCT25G11 ZCT28N12 ZCMD21M12 ZCP21M12 ZCD28 ZCMD61C12 ZCT27N12 ZCMD21C12 ZCMD81L5 ZCT27G11 ZCT26P16 ZCMD21L2 ZCT25N12 ZCP25 ZCP29M12 ZCT27P16 ZCT21P16 ZCD35 ZCMD41L2

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCD29M12
 ZCMD25L5
 ZCMD21L08U78
 ZCT21G11
 ZCT28G11
 ZCP31
 ZCMD37L5
 ZCD29
 ZCT26N12
 ZCMD39L2
 ZCP21
 ZCT25P16
 ZCP37
 ZCMD61M12
 ZCD37
 ZCP39
 ZCMD25L2
 ZCMD37L2
 ZCP35
 ZCT26G11
 ZCD26
 ZCMD41L1
 ZCD25
 ZCMD29L1
 ZCMD39L1
 ZCP27
 ZCMD41L5
 ZCMD81L2
 ZCD31
 ZCMD37L1
 ZCMD21L1
 ZCMD29L5
 ZCMD25L1
 ZCMD21L5
 ZCT28P16
 ZCD21
 ZCP28
 ZCMD81L1
 ZCT21N12
 ZCMD21L08R12

Movement of operating head	Linear
Type of operator	Roller lever plunger spring return metal retractable)
Type of approach	Lateral approach, 1 direction

Complementary

Switch actuation	By 30° cam
Positive opening	With

Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.07 lb(US) (0.030 kg)
Package 1 Height	0.200 dm
Package 1 width	0.500 dm
Package 1 Length	0.350 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration

Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------