Rittal – The System.

Faster – better – everywhere.

Wall-Mounted Housing WM Stainless steel – WM 8017.600

Date : Mar 9, 2015



ENCLOSURES

POWER DISTRIBUTION >> CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Wall-Mounted Housing WM Stainless steel – WM 8017.600 - WM242408N4

created : 09.03.2015 build on www.rittal.com/ca-en



Product description

Material:	Door: Stainless steel, all-round foamed-in PU seal Housing and door: Stainless steel 1.4301 (AISI 304) Mounting plate: Carbon steel, zinc-plated
Surface finish:	Brushed
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4X
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Wall mounting blind-nuts
Packaging unit:	1 pc(s).
Product features	
Dimensions:	Height: 600 mm(24 ″) Width: 600 mm(24 ″) Depth: 210 mm(8.3 ″)
Mounting plate:	Height: 570 mm(22 ″) Width: 549 mm(22 ″)
	26 kg (57.3 lb.)

Approvals	
Approvals:	⊠ <u>UL + C-UL (US)</u>
Downloads	
Data sheets:	[™] <u>Graphics (US)</u>
Documentation:	Info sheet (US)
CAD drawings:	Request