# NSYCR10WU2C

# ClimaSys PTC heating resistance 10W,110-250V insulate





# Main Range ClimaSys Product name ClimaSys CR Product or Component Resistance heater Type Power range 10 W Input voltage 110...250 V AC 50/60 Hz

2 screw terminals 2.5 mm<sup>2</sup>

### Complementary

Operating position	Vertical	
Ambient Air Temperature for Operation	-40158 °F (-4070 °C)	
IP Degree of Protection	IP20	
Electrical Insulation Class	Class II	
Product Certifications	VDE[RETURN]UL	
Material	Body extruded aluminium Cover plastic	
Height	External 3.86 in (98 mm)	
Width	External 1.50 in (38 mm)	
Depth	External 2.95 in (75 mm)	
Condition of use	Electrical protection is needed Air sealed enclosure Heaters must be installed with a thermal controller	
Fixing Mode	By clips	
Mounting Support	35 mm DIN rail	

Electrical connection

### Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES		
Discount Schedule	ES1		
GTIN	3606480152252		
Returnability	No		
Country of origin	ES		

### **Packing Units**

r doming office		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.77 in (4.5 cm)	
Package 1 Width	3.15 in (8.0 cm)	
Package 1 Length	4.33 in (11.0 cm)	
Package 1 Weight	5.64 oz (160.0 g)	
Unit Type of Package 2	CAR	
Number of Units in Package 2	50	
Package 2 Height	7.48 in (19.0 cm)	
Package 2 Width	15.75 in (40.0 cm)	

Package 2 Length	23.62 in (60.0 cm)
Package 2 Weight	20.86 lb(US) (9.46 kg)
Unit Type of Package 3	PAM
Number of Units in Package 3	500
Package 3 Height	20.08 in (51.0 cm)
Package 3 Width	39.37 in (100.0 cm)
Package 3 Length	47.24 in (120.0 cm)
Package 3 Weight	252.65 lb(US) (114.6 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

### Contractual warranty

Warranty	18 months	