

# VuLite® 6" Line Voltage Housings and Trims

Economy Recessed Lighting

## IC Housings


### V61CW 6" IC New Construction V61CNW 6" IC New Construction with Floating Socket



Energy efficient housing.  
May be covered with insulation.

Dimensions:  
13-3/4"L x 13-3/8"W x 7-3/8"H

Ceiling Cutout: 6-1/2" Dia.




### V61CRW 6" IC Remodel



Energy efficient housing.  
May be covered with insulation.

Dimensions:  
13-3/4"L x 6-3/4"W x 7-3/8"H

Ceiling Cutout: 6-1/4" Dia.



Accessories: **VALG4** Airloc® gasket kit for V41C housing when an Airloc® trim is not being used.  
**G2405** Set of (4) T-bar clips for installation in suspended ceilings.


## TC Housings

### V6TCW 6" TC New Construction

Requires 3" spacing from insulation.

Dimensions:  
13-3/4"L x 13-3/8"W x 7-3/8"H

Ceiling Cutout: 6-1/2" Dia.




### V6TCRW 6" TC Remodel

Requires 3" spacing from insulation.

Dimensions:  
13-3/4"L x 6-3/4"W x 7-3/8"H

Ceiling Cutout: 6-1/4" Dia.




## 6" Compatible Trims

### Conical Baffle

V3024W-WH: White  
V3024B-WH: Black

Aperture: 5-3/4"  
Outer Diameter: 7-3/4"



#### VuLite Housing: Lamp Wattage/Type

V61CW, V61CRW: 50W PAR30, 75W PAR30L, 65W BR30  
V6TCW, V6TCRW: 75W PAR30/PAR30L, 65W BR30, 120W BR40


#### Juno Compatible Housing: Lamp Wattage/Type

IC22, IC22R: 50W PAR30, 75W PAR30L, 65W BR30  
IC2, TC2, TC2R: 75W PAR30 w/socket extender, 75W PAR30L, 65W BR30

### Straight Baffle

V3025W-WH: White  
V3025B-WH: Black

Aperture: 5-3/4"  
Outer Diameter: 7-3/4"



#### VuLite Housing: Lamp Wattage/Type

V61CW, V61CRW: 50W PAR30/PAR30L, 75W PAR38  
V6TCW, V6TCRW: 75W PAR30/PAR30L, 65W BR30, 120W BR40, 120W PAR38

#### Juno Compatible Housing: Lamp Wattage/Type

IC22, IC22R: 75W PAR30/PAR30L, 65W BR30, 75W PAR38  
IC2: 75W PAR30 w/socket extender, 75W PAR30L, 65W BR30, 90W PAR38, 100W BR40  
TC2, TC2R: 75W PAR30 w/socket extender, 75W PAR30L, 65W BR30, 150W PAR38, 120W BR40

### Full Baffle

V3034W-WH: White  
V3034B-WH: Black  
V3034TW-WH: White w/Torsion Springs  
V3034TB-WH: Black w/Torsion Springs

Aperture: 5-3/4"  
Outer Diameter: 7-5/8"



#### VuLite Housing: Lamp Wattage/Type

V61CW, V61CNW, V61CRW: 40W A19\*, 75W PAR30/PAR30L, 65W BR30, 90W BR40, 90W PAR38\*  
V6TCW, V6TCRW: 60W A19\*, 75W PAR30/PAR30L, 85W BR30, 120W BR40, 150W PAR38\*

\* No A19 listing and 75W PAR38 max. for the V3034B Series

#### Juno Compatible Housing: Lamp Wattage/Type

IC22, IC22R, IC23: 40W A19, 75W PAR30/PAR30L, 65W BR30, 90W BR40, 90W PAR38  
IC2: 60W A19, 75W PAR30/PAR30L, 85W BR30, 100W PAR38, 120W BR40  
TC2, TC2R: 60W A19, 75W PAR30/PAR30L, 85W BR30, 150W PAR38, 120W BR40  
ICPL6 Series: 32W max. CFLT  
PL6 Series: 42W max CFLT

†Note: For best performance, 26W is recommended.

Patent Pending

### Clear Cone

V3027C-WH: Clear

Aperture: 5-3/4"  
Outer Diameter: 7-3/4"



#### VuLite Housing: Lamp Wattage/Type

V61CW, V61CRW: 50W PAR30, 75W PAR30L, 65W BR30  
V6TCW, V6TCRW: 75W PAR30/PAR30L, 65W BR30, 90W BR40

#### Juno Compatible Housing: Lamp Wattage/Type

IC2, IC22, IC22R: 50W PAR30, 75W PAR30L, 65W BR30  
TC2, TC2R: 75W PAR30/PAR30L, 65W BR30