## Product data sheet Characteristics

## NSYMM86

# Plain mounting plate H800xW600mm made of galvanised sheet steel





#### Overview

Lead time Usually Ships within 4 Weeks
--

#### Main

Range	Spacial	
Accessory / separate part category	Mounting accessory	
Product or Component Type	Mounting plate	
Device Application	Multi-purpose	
Enclosure nominal dimensions	- H: 31.50 in (800 mm) W: 23.62 in (600 mm)	
Mounting Location	Step slide Direct fixing on backstuds	
Mounting plate description	Plain	
Range compatibility	Spacial Spacial S3D Spacial Spacial CRN Spacial Spacial S3X Thalassa Thalassa PLM	
Quantity per Set	Set of 1	
Material	Galvanised steel	

#### Complementary

Fixing mode	Screwed on backstuds M8 By fixing element	
Permanent permissible load	297.62 lb(US) (135 kg)	
Height	29.53 in (750 mm)	
Width	21.65 in (550 mm)	
Thickness	0.10 in (2.5 mm)	
Net Weight	17.79 lb(US) (8.07 kg)	
Variant particularity	With enclosures H800 x W1200	

### Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480183430
Returnability	Yes
Country of origin	ES
	-

## Packing Units

	DOE.
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.39 in (1.0 cm)
Package 1 Width	21.65 in (55.0 cm)
Package 1 Length	29.53 in (75.0 cm)
Package 1 Weight	19.38 lb(US) (8.792 kg)
Unit Type of Package 2	PAM
Number of Units in Package 2	60
Package 2 Height	17.72 in (45.0 cm)
Package 2 Width	39.37 in (100.0 cm)
Package 2 Length	47.24 in (120.0 cm)
Package 2 Weight	1191.64 lb(US) (540.52 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<sup>™</sup> China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

### Contractual warranty

Warranty	18 months