

# ZB5AC180

Head for push button, Harmony XB5, XB4, pushbutton harsh environment, white, without marking



## Main

|                                 |                                          |
|---------------------------------|------------------------------------------|
| Range of Product                | Harmony XB5                              |
| Product or Component Type       | Head for push-button                     |
| Device short name               | ZB5                                      |
| Bezel material                  | Black plastic                            |
| Head type                       | Standard                                 |
| Mounting diameter               | 0.87 in (22 mm)                          |
| Sale per indivisible quantity   | 1                                        |
| Shape of signaling unit head    | Round                                    |
| Type of operator                | Spring return                            |
| Operator additional information | Vertical mounting<br>Horizontal mounting |

## Complementary

|                                    |                                                                                                                                                                                                |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAD overall width                  | 1.46 in (37 mm)                                                                                                                                                                                |
| CAD overall height                 | 0.73 in (18.5 mm)                                                                                                                                                                              |
| CAD overall depth                  | 1.46 in (37 mm)                                                                                                                                                                                |
| Net Weight                         | 0.05 lb(US) (0.024 kg)                                                                                                                                                                         |
| Resistance to high pressure washer | 0.01 psi (90 Pa) 180 °F (82.5 °C)                                                                                                                                                              |
| Operator profile                   | White flush, unmarked                                                                                                                                                                          |
| Mechanical durability              | 10000000 cycles                                                                                                                                                                                |
| Electrical composition code        | C1 9 single front mounting<br>C2 9 single and double front mounting<br>C11 3 single front mounting<br>C15 1 single front mounting<br>SF1 3 single front mounting<br>SR1 3 single rear mounting |
| Device presentation                | Basic element                                                                                                                                                                                  |

## Environment

|                                       |                                                         |
|---------------------------------------|---------------------------------------------------------|
| Ambient Air Temperature for Storage   | -40...185 °F (-40...85 °C)                              |
| Ambient Air Temperature for Operation | -40...158 °F (-40...70 °C)                              |
| Electrical shock protection class     | Class II IEC 61140                                      |
| IP degree of protection               | IP66 IEC 60529<br>IP69K<br>IP67                         |
| NEMA degree of protection             | NEMA 4 UL 508<br>NEMA 13<br>NEMA 12                     |
| IK degree of protection               | IK03 IEC 62262                                          |
| Standards                             | UL 508<br>IEC 60947-5-1<br>IEC 60947-1<br>CSA C22.2     |
| Product Certifications                | CSA[RETURN]UL[RETURN]CE                                 |
| Vibration resistance                  | 5 gn 2...500 Hz)IEC 60068-2-6                           |
| Shock resistance                      | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 |

## Ordering and shipping details

|                   |                                     |
|-------------------|-------------------------------------|
| Category          | 22467-PUSHBUTTONS,22MM(PLASTIC) NEW |
| Discount Schedule | CS2                                 |
| GTIN              | 3606480444791                       |
| Returnability     | No                                  |
| Country of origin | FR                                  |

## Packing Units

|                              |                  |
|------------------------------|------------------|
| Unit Type of Package 1       | PCE              |
| Number of Units in Package 1 | 1                |
| Package 1 Height             | 1.46 in (3.7 cm) |
| Package 1 Width              | 1.46 in (3.7 cm) |
| Package 1 Length             | 1.46 in (3.7 cm) |
| Package 1 Weight             | 0.85 oz (24.0 g) |

## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                       |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                                 |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                     |
| REACH free of SVHC         | Yes                                                                                                                                                                                                                                                                                   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>                                                                                                                                                                                        |
| Toxic heavy metal free     | Yes                                                                                                                                                                                                                                                                                   |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                                                                                                                                                                                |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                                   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                                                         |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                                                                                                                                                                                                               |


## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---

Dimensions

---



## Installation on Flat Surface

### Without Protective Guard



(1) Ø22.5 mm recommended ( $\text{Ø}22.3_0^{+0.4}$ ) / Ø0.89 in. recommended ( $\text{Ø}0.88_0^{+0.016}$ )

### With Protective Guard



(1) Ø22.5 mm recommended ( $\text{Ø}22.3_0^{+0.4}$ ) / Ø0.89 in. recommended ( $\text{Ø}0.88_0^{+0.016}$ )

---

Electrical Composition Corresponding to Code C1

---



---

Electrical Composition Corresponding to Code C2

---



---

Electrical Composition Corresponding to Codes C9, C11, SF1 and SR1

---



---


Electrical Composition Corresponding to Code C15

---


1 N/O



1 N/C



1 N/O + N/C or 1 N/O + N/O or 1 N/C + N/C



---

Legend

---

Single contact



Double contact



Light block



Possible location

