

TS 35X15/LL 2M/ST/SZ

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Product image



Steel DIN rails are the most widespread on the market. Among metal DIN rails, they have the lowest shortcircuit protection, similar to stainless steel.

General ordering data

| | |
|------------|---|
| Version | Terminal rail, Accessories, Steel, galvanic zinc plated and passivated, Width: 2000 mm, Height: 35 mm, Depth: 15 mm, Slit width: 5.20 mm, Slit length: 25.00 mm |
| Order No. | 7907490000 |
| Type | TS 35X15/LL 2M/ST/SZ |
| GTIN (EAN) | 4032248296262 |
| Qty. | 2 m |

Date de création 26 novembre 2024 14:14:17 CET

Niveau du catalogue 26.11.2024 / Toutes modifications techniques réservées

TS 35X15/LL 2M/ST/SZ

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Caractéristiques techniques

Dimensions and weights

| | | | |
|------------|----------|-----------------|------------|
| Depth | 15 mm | Depth (inches) | 0,591 inch |
| Height | 35 mm | Height (inches) | 1,378 inch |
| Width | 2 000 mm | Width (inches) | 78,74 inch |
| Net weight | 624 g | | |

Mounting rail

| | | |
|--|-------------------------------------|----------|
| Drill-hole diameter | 5,2 mm | |
| Installation advice | Direct mounting | |
| Length of the terminal rail | min. | 0 mm |
| | nominal | 2 000 mm |
| | max. | 2 000 mm |
| Material | Steel | |
| Pre-punched mounting rail | Yes | |
| Short circuit strength corresponds to E-Cu wire | 50 mm ² | |
| Short-time withstand current per second according to IEC 60947-7-2 | 6 kA | |
| Slit gap | 11 mm | |
| Slit gap | | |
| Slit length | 25 mm | |
| Slit length | | |
| Slit width | 5,2 mm | |
| Slit width | | |
| Slotted drill holes | Yes | |
| Solder eyelet hole diameter (D) | 5,2 mm | |
| Spacing of holes, centre-to-centre | 36 mm | |
| Standards | In accordance with DIN EN 60715 | |
| Surface finish | galvanic zinc plated and passivated | |
| Thickness | 1,5 mm | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC001285 | ETIM 7.0 | EC001285 |
| ETIM 8.0 | EC001285 | ETIM 9.0 | EC001285 |
| ECLASS 9.0 | 27-40-06-02 | ECLASS 9.1 | 27-40-06-02 |
| ECLASS 10.0 | 27-40-06-02 | ECLASS 11.0 | 27-40-06-02 |
| ECLASS 12.0 | 27-40-06-02 | ECLASS 13.0 | 27-40-06-02 |
| ECLASS 14.0 | 27-40-06-02 | | |

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

Important note

| | |
|---------------------|--|
| Product information | Din rails with Sendzimier treatment have limited corrosion resistance on the outer and cut edges |
|---------------------|--|

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Fiche de données**TS 35X15/LL 2M/ST/SZ**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Caractéristiques techniques**Downloads**

| | |
|--------------------|---|
| Engineering Data | CAD data – STEP |
| User Documentation | StorageConditionsTerminalBlocks |
| Catalogues | Catalogues in PDF-format |

Fiche de données**TS 35X15/LL 2M/ST/SZ**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Dessins