

Main

Ampere Rating	100mA
Ampere Rating	100mA
Approvals	UL Listed File Number: E164869 CCN NRKH - CSA Certified - CE Marked
Approvals	UL Listed File Number: E164869 CCN NRKH - CSA Certified - CE Marked
Body Type	Flat Rectangular
Body Type	Flat Rectangular
Connection Type	Cable (10m)
Connection Type	Cable (10m)
Depth	8mm
Depth	8mm
Enclosure Material	PBT (Case) - PVR (Cable)
Enclosure Material	PBT (Case) - PVR (Cable)
Enclosure Rating	NEMA 4X/12
Enclosure Rating	NEMA 4X/12
Enclosure Type	Water tight, Dust tight and Corrosion Resistant
Enclosure Type	Water tight, Dust tight and Corrosion Resistant
Height	32mm
Height	32mm
LED Indicator	Output: Yellow
LED Indicator	Output: Yellow
Marketing Trade Name	Osiprox
Marketing Trade Name	Osiprox
Maximum Operating Frequency	2000Hz
Maximum Operating Frequency	2000Hz
Maximum Voltage Rating	36VDC
Maximum Voltage Rating	36VDC
Nominal Sensing Distance	5mm
Nominal Sensing Distance	5mm
Operating Temperature Range	-13 to 158 Degrees F (-25 to 70 Degrees C)
Operating Temperature Range	-13 to 158 Degrees F (-25 to 70 Degrees C)
Output	DC 3-Wire (PNP) - 1 N.O.
Output	DC 3-Wire (PNP) - 1 N.O.
Size	F
Size	F
Supply Voltage	12/24VDC
Supply Voltage	12/24VDC
Type	XS7
Type	XS7
Width	15mm
Width	15mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.