

FEATURES & SPECIFICATIONS

INTENDED USE — Ideal one-for-one replacement of conventional HID and fluorescent high bay systems. Applications include warehousing, manufacturing, gymnasiums, and other large indoor spaces with mounting heights up to 60'. **Certain airborne contaminants can diminish the integrity of acrylic and/or polycarbonate.** [Click here for Acrylic-Polycarbonate Compatibility table for suitable uses.](#)

CONSTRUCTION — Lightweight aluminum heat sink designed to perform in ambient temperatures up to 55 °C for maximum naturally convective cooling. Structural elements such as the channel and end caps are fabricated from steel for maximum rigidity. Wireguard attachment points provided.

OPTICS — General, narrow, wide and focus distributions available to meet both horizontal and vertical light level requirements. Injection molded refractors for repeatable photometry. Diffuse lens standard to provide glare control and LED protection.

ELECTRICAL — L88 at 60,000 hours, L70>100,000 hours. Utilizes a 90°C case temperature driver for maximum life at high temperatures. 0.90 power factor and 3kA/6kV level of surge protection is standard. Optional 5kA/10kV surge protection available. Available as 120-277V or 347-480V input.

0-10V dimming standard for a dimming range of 100% to 10%.

WIRELESS NETWORKING — XPoint™ Wireless technology creates a mesh network to ensure communication between fixtures, sensors and wall stations facility-wide. This option provides superior lighting management capabilities including granular control, configuration and custom grouping for increased energy savings.

INSTALLATION — Suitable for suspension by chain, cable, surface-mounting bracket (THUN accessory), hook monopoint or single (pendant) monopoint. Surface mounting not recommended without optional surface mounting bracket. To maintain ambient listing, fixture should be mounted at a minimum plenum height of 18".

LISTINGS — CSA certified to US and Canadian safety standards. Damp location listed. Suitable for ambient temperatures from -40°F (-40°C) to 113°F (45°C) when suspended 18" from ceiling. High ambient option available (HA), suitable for ambient temperatures -40°F (-40°C) to 131°F (55°C) when suspended 18" from ceiling. IP5X rated.

DesignLights Consortium® (DLC) Premium qualified product and DLC qualified product. Not all versions of this product may be DLC Premium qualified or DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

WARRANTY — 5-year limited warranty. Complete warranty terms located at: www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Stock configurations are offered for shorter lead times:

Standard Part Number	Stock Part Number
IBG 12000LM SEF AFL GND MVOLT OZ10 40K 80CRI DWH	IBG 12L MVOLT
IBG 15000LM SEF AFL GND MVOLT OZ10 40K 80CRI DWH	IBG 15L MVOLT
IBG 18000LM SEF AFL GND MVOLT OZ10 40K 80CRI DWH	IBG 18L MVOLT
IBG 24000LM SEF AFL GND MVOLT OZ10 40K 80CRI DWH	IBG 24L MVOLT
IBG 12000LM SEF AFL GND HVOLT OZ10 40K 80CRI DWH	IBG 12L HVOLT
IBG 15000LM SEF AFL GND HVOLT OZ10 40K 80CRI DWH	IBG 15L HVOLT
IBG 18000LM SEF AFL GND HVOLT OZ10 40K 80CRI DWH	IBG 18L HVOLT
IBG 24000LM SEF AFL GND HVOLT OZ10 40K 80CRI DWH	IBG 24L HVOLT
IBG 12000LM SEF AFL GND MVOLT OZ10 50K 80CRI DWH	IBG 12L MVOLT 5K
IBG 15000LM SEF AFL GND MVOLT OZ10 50K 80CRI DWH	IBG 15L MVOLT 5K
IBG 18000LM SEF AFL GND MVOLT OZ10 50K 80CRI DWH	IBG 18L MVOLT 5K
IBG 24000LM SEF AFL GND MVOLT OZ10 50K 80CRI DWH	IBG 24L MVOLT 5K
IBG 12000LM SEF AFL GND HVOLT OZ10 50K 80CRI DWH	IBG 12L HVOLT 5K
IBG 15000LM SEF AFL GND HVOLT OZ10 50K 80CRI DWH	IBG 15L HVOLT 5K
IBG 18000LM SEF AFL GND HVOLT OZ10 50K 80CRI DWH	IBG 18L HVOLT 5K
IBG 24000LM SEF AFL GND HVOLT OZ10 50K 80CRI DWH	IBG 24L HVOLT 5K

Catalog Number
Notes
Type

LED High Bay

IBG



A+ Capable Luminaire

This item is an A+ capable luminaire, which has been designed and tested to provide consistent color appearance and out-of-the-box control compatibility with simple commissioning.

- All configurations of this luminaire meet the Acuity Brands' specification for chromatic consistency
- This luminaire is part of an A+ Certified solution for nLight® or XPoint™ Wireless control networks marked by a **shaded background***

To learn more about A+, visit www.acuitybrands.com/aplus.

*See ordering tree for details

IBG LED High Bay



A+ Capable options indicated by this color background.

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: IBG 24000LM SEF AFL GND MVOLT OZ10 40K 80CRI DWH

IBG																		
Series	Lumens					Performance package		Lens		Distribution		Voltage		Driver		Color temperature		
IBG	8000LM	8,000 lumens	30000LM	30,000 lumens		SEF	Standard efficiency	AFL	Acrylic, frosted	WD	Wide	MVOLT	120-277V			30K	3000 K	
IBGN ¹	12000LM	12,000 lumens	36000LM	36,000 lumens		HEF	Premium efficiency	ACL	Clear acrylic	GND	General	HVOLT	347-480V ²		0-10V dimming	35K	3500 K	
	15000LM	15,000 lumens	48000LM	48,000 lumens				PCL	Clear polycarbonate	ND	Narrow		120	120V			40K	4000 K
	18000LM	18,000 lumens	60000LM	60,000 lumens				PFL	Semi-diffuse polycarbonate	FD	Focus		208	208V			50K	5000 K
	24000LM	24,000 lumens											240	240V				
									L/LENS	Less lens				277		277V		
													347	347V ³				
													480	480V ^{3,4}				

Coloring rendering index	Options						Finish	
70CRI 70 CRI 80CRI 80 CRI 90CRI 90 CRI	HA SPD BPK PS1050 PS10250 PS30250 BGTD SF DF OUTCTR OCS OCU____ IMP RRL____ WGX	High ambient ⁵ Surge protection device ⁶ Fixture backpack ⁷ Emergency battery pack ⁸ Emergency battery pack ⁹ Emergency battery pack ¹⁰ Generator transfer device ¹¹ Single fuse ¹² Double fuse ¹³ Wiring leads pulled through back center of fixture ¹⁴ RELOC® OnePass® selectable cable 6' installed ^{15, 16} RELOC® OnePass® unselectable cable 6' installed (must specify tap position) ¹⁵ Integrated modular plug ¹⁷ RELOC®-Ready luminaire. See page 10 for ordering information Standard wire guard, installed	<u>Cord sets:</u> CS1W CS3W CS7W CS11W CS25W CS97W CS93W CS93W5CD	Straight plug, 120V ¹⁵ Twist-lock, 120V ¹⁵ Straight plug, 277V ¹⁵ Twist-lock, 277V ¹⁵ Twist-lock, 347V ¹⁵ Twist-lock, 480V ¹⁵ 600 SO white cord, no plug (no voltage required) 600 SO 5-conductor white cord, no plug (no voltage required)	<u>Controls:</u> ¹⁵ LCOZU LCHOSZU LCPZU LAOZU LAHOSZU LAPZU LAMOSZU LCMOSZU C6DOSUEM C10DOSUEM nPP16D nPP16DER nMSI nMSI360 nMSID nMSI360D MSI6XADL DSCXADL XPW XAD	High mount aisleway motion sensor, pre-wired High mount aisleway motion sensor with dimming, pre-wired High mount aisleway motion sensor with photocell, pre-wired 360° high mount motion sensor, pre-wired 360° high mount motion sensor with dimming, pre-wired 360° high mount motion sensor with photocell, pre-wired 360° high mount motion sensor, dimming & switching photocell, pre-wired High mount aisleway motion sensor, dimming & switching photocell, pre-wired 360° high mount motion sensor, dimming & switching photocell capable, pre-wired; UL924 listed ¹⁸ 360° low mount motion sensor, dimming & switching photocell capable, pre-wired; UL924 listed ¹⁸ nLight® dimming & switching module ¹⁹ nLight® dimming & switching module with emergency relay ¹⁹ nLight® high mount aisleway motion sensor, pre-wired ¹⁹ nLight® 360° high mount motion sensor, pre-wired ¹⁹ nLight® high mount aisleway motion sensor with dimming, pre-wired ¹⁹ nLight® 360° high mount motion sensor with dimming, pre-wired ¹⁹ XPoint™ Wireless 360° high mount motion sensor with photocell XPoint™ Wireless 0-10V relay, external (utilizes XPA CMRBO) 55°C max ambient ²⁰ XPoint™ Wireless 0-10V relay, internal, lower max ambient ^{20,21}	DNA DWH	Natural aluminum Gloss white

See Accessories and footnotes on next page

IBG LED High Bay

Accessories: Order as separate catalog number.					
Mounting:		Cord sets and sensors for IMP option:		Wire guards:	
IBAC120 M20	Aircraft cable 10' with hook (one pair)	CS1WIMP	Straight plug, 120V	WGIBG22	Wire guard for IBG 2ft 2-module, gloss white
IBAC240 M20	Aircraft cable 20' with hook (one pair)	CS3WIMP	Twist-lock, 120V	WGIBG24	Wire guard for IBG 2ft 4-module, gloss white
IBHMP	Hook monopoint	CS7WIMP	Straight plug, 277V	WGIBG26	Wire guard for IBG 2ft 6-module, gloss white
HBBS36	Chain hanger with chain, 36" (one pair)	CS11WIMP	Twist-lock, 277V	WGIBG42	Wire guard for IBGN 4ft 2-module, gloss white
IBGACVH	Aircraft 10' V hanger (one pair)	CS25WIMP	Twist-lock 347V	WGIBG46	Wire guard for IBG 4ft 6-module, gloss white
IBGPMPHB	Pendant monopoint splice box, includes side covers (3/4" hub) for use with OUTCTR option	CS93WIMP	600V SO white cord, no plug (no voltage required)	WGIBG22DNA	Wire guard for IBG 2ft 2-module, natural aluminum
HC36	Chain hanger and jack chain (pair)	CS97WIMP	Twist-lock 480V	WGIBG24DNA	Wire guard for IBG 2ft 4-module, natural aluminum
THUN	Tong hanger bracket (order 2 per fixture)	IBGMSIIMP	Aisle sensor for use with IMP option	WGIBG26DNA	Wire guard for IBG 2ft 6-module, natural aluminum
		IBGMSI360IMP	360° sensor for use with IMP option	WGIBG42DNA	Wire guard for IBGN 4ft 2-module, natural aluminum
				WGIBG46DNA	Wire guard for IBG 4ft 6-module, natural aluminum

Notes

- Available with 18000LM, 24000LM, 30000LM and 36000LM only.
- Not available with 8000LM. Not available with BTGD, nPP16D, nPP16DER, PS1050, PS10250, PS30250 or XAD.
- When ordered with 8000LM voltage selected utilizes the fixture back pack.
- Not available with nPP16D or nPP16DER.
- 55 C when suspended, 45 C when surface mounted. Not available with BGTD, PS1050, PS10250, PS30250, XAD, or XPW.
- Standard with HVOLT, 347, or 480V - only specify for MVOLT, 120, 208, 240, or 277V. Standard with Motion sensors/controls, BGTD & Power Sentry battery options.
- Required with PS1050, PS10250, PS30250, BGTD. Required with 8000LM when ordered with 347/480V. Required with Xpoint controls when order with 347/480V. Not available with nLight. Not for use with THUN mount (surface).
- Requires BPK option. Available 120-277V only. Available with 8000LM only. For ambient temperatures of 32°F to 122°F (0°C to 50°C).
- Requires BPK option. Available 120-277V only. Not available with 8000LM. For ambient temperatures of 50°F to 122°F (10°C to 50°C).
- Requires BPK option. 120 or 277V only. Not available with 8000LM. For ambient temperatures of 32°F to 122°F (0°C to 50°C).
- Requires BPK option. 120 or 277V only. Not available with PS1050, PS10250, PS30250. Not available with 347 or 480V when ordered in combination with XAD or XPW. For ambient temperatures up to 113°F(45°C).
- Available on 120, 277, 347V. Not available with MVOLT or HVOLT.
- Available on 208, 240, 480V. Not available with MVOLT or HVOLT.
- Not available with BPK option. Requires IBGPMPHB accessory to mount fixture. Not available with Cord Set options.
- Must specify voltage.
- Cannot be used in dimming applications, must use RRLC125
- Not available with BPK, nPP16D, nPP16DER, nMSI, or nMSI360.
- Daylight harvesting functionality not enabled by default. See page 9 for default sequence of operation.
- Not available with 208V, 240V, or 480V.
- Not available with HVOLT. When ordered with 347or 480V BPK option is required. Requires SPD option if ordered with MVOLT, 120, 208, 240, or 277V.
- Not available with HA option.

POWER SENTRY EMERGENCY BATTERY PACKS


PS1050:	http://www.acuitybrands.com/products/detail/369448/Power-Sentry/PS1050/Reduced-Profile-LED-Emergency-Battery-Pack/-/media/products/Power_Sentry/369448/document/PS1050_.pdf.pdf
PS10250:	http://www.acuitybrands.com/products/detail/604737/Power-Sentry/PS10250/Emergency-LED-Battery-Backup/-/media/products/Power_Sentry/604737/document/PS10250_.pdf.pdf
PS30250:	http://www.acuitybrands.com/products/detail/604739/Power-Sentry/PS30250/Emergency-LED-Battery-Backup/-/media/products/Power_Sentry/604739/document/PS30250_.pdf.pdf

IBG LED High Bay

DIMENSIONS

All dimensions are in inches (centimeters) unless otherwise indicated.
Dimensions may vary with options or accessories.

Weight: (may vary with options or accessories)
8L: 7.75 lbs (3.515Kg)
12L/15L: 10.5 lbs (4.762Kg)
18L/24L/30L: 15.9 lbs (7.212Kg)
18L/24L/30L/36L: 4' Narrow - 16.25 lbs (7.370Kg)
36L/48L/60L: 4' - 6' Mod - 21.75 lbs (9.865Kg)



IBG OPERATIONAL DATA

	Lumen package	Efficiency level	Lens/distribution			
			Acrylic frosted/ general	Clear acrylic/narrow	Clear acrylic/wide	Clear acrylic/focus
Delivered lumens 4000K, 80CRI	8000LM	SEF	7594	7145	7384	7364
		HEF	7842	7378	7625	7604
	12000LM	SEF	11580	10895	11260	11228
		HEF	11746	11051	11421	11390
	15000LM	SEF	14458	13603	14059	14019
		HEF	14824	13947	14415	14374
	18000LM	SEF	17329	16303	16850	16803
		HEF	17752	16702	17262	17214
	24000LM	SEF	23000	21639	22365	22303
		HEF	23612	22215	22960	22896
	30000LM	SEF	27344	25727	26589	26515
		HEF	29577	27827	28760	28680
	36000LM	SEF	33203	31239	34547	32197
		HEF	35528	33426	34547	34450
	48000LM	SEF	45973	43253	44704	44579
		HEF	47254	44458	45949	45821
60000LM	SEF	55453	52172	53922	53771	
	HEF	57027	53653	55452	55298	
Delivered lumens 5000K, 80CRI	8000LM	SEF	7873	7408	7656	7635
		HEF	8082	7604	7859	7837
	12000LM	SEF	12006	11296	11674	11642
		HEF	12106	11390	11771	11739
	15000LM	SEF	14990	1413	14576	14536
		HEF	15278	14374	14856	14815
	18000LM	SEF	17966	16904	17470	17422
		HEF	18296	17214	17791	17741
	24000LM	SEF	23847	22436	23188	23123
		HEF	24366	22896	23664	23598
	30000LM	SEF	28351	26674	27568	27491
		HEF	30483	28680	29641	29559
	36000LM	SEF	34221	32196	35605	33183
		HEF	36616	34450	35605	35506
	48000LM	SEF	47665	44845	46349	46220
		HEF	48702	45820	47357	47225
60000LM	SEF	57494	54093	55906	55751	
	HEF	58774	55297	57151	56992	

PHOTOMETRICS

See www.lithonia.com.

IBG CHARACTERISTICS

Lumen package	Wattage								Length	Width	Depth	Comparable Light Source
	Standard efficiency				High efficiency							
	120V	277V	347V	480V	120V	277V	347V	480V	Dimensions are shown in inches (centimeters) unless otherwise noted.			
8000LM	55	54	58	61	50	49	51	54	25.6	11.75	2.75	100W MH, 4-lamp T8 NBF
12000LM	79	77	77	76	70	69	68	67	25.6	15.52	2.75	175W MH, 4-lamp T8 HBF, 2-lamp T5HO
15000LM	97	95	97	96	87	86	86	86	25.6	15.52	2.75	200W MH, 6-lamp T8 NBF
18000LM	114	112	114	115	102	100	102	103	25.6	20.65	2.75	250W MH, 6-lamp T8 HBF, 4-lamp T5HO
24000LM	154	150	150	150	136	133	135	135	25.6	20.65	2.75	400W MH, 6-lamp T5HO
30000LM	193	186	188	188	176	171	173	173	25.6	20.65	2.75	575W MH, 10-lamp T8 HBF
36000LM	225	221	227	229	200	197	203	206	47.29	20.65	2.75	750W MH, 8-lamp T5HO
48000LM	301	293	301	302	267	261	269	270	47.29	20.65	2.75	875W MH, 10-lamp T5HO
60000LM	385	374	378	377	332	323	330	330	47.29	20.65	2.75	1000W MH

IBGN OPERATIONAL DATA

	Lumen package	Efficiency level	Lens/distribution			
			Acrylic frosted/ general	Clear acrylic/narrow	Clear acrylic/wide	Clear acrylic/focus
Delivered lumens 4000K, 80CRI	18000LM	SEF	17036	16028	16566	16520
		HEF	17776	16724	17285	17237
	24000LM	SEF	22727	21383	22100	22038
		HEF	24123	22696	23457	23392
	30000LM	SEF	28642	26948	27851	27773
		HEF	29493	27748	28679	28599
	36000LM	SEF	34336	32305	33388	33295
		HEF	34912	32846	33948	33853
Delivered lumens 5000K, 80CRI	18000LM	SEF	17663	16618	17175	17128
		HEF	18320	17237	17814	17765
	24000LM	SEF	23564	22170	22913	22849
		HEF	24862	23391	24176	24108
	30000LM	SEF	29696	27940	28876	28796
		HEF	30397	28599	29558	29475
	36000LM	SEF	35600	33494	34617	34520
		HEF	35982	33853	34988	34890

IBGN CHARACTERISTICS

Lumen package	Wattage								Length	Width	Depth
	Standard efficiency				High efficiency						
	120V	277V	347V	480V	120V	277V	347V	480V	Dimensions are shown in inches (centimeters) unless otherwise noted.		
18000LM	117	114	115	114	104	102	101	101	47.29	11.75	2.75
24000LM	172	170	167	167	152	150	153	153	47.29	11.75	2.75
30000LM	209	205	208	207	183	180	179	178	47.29	11.75	2.75
36000LM	246	240	242	243	207	203	202	201	47.29	11.75	2.75

PROJECTED LUMEN MAINTENANCE

IBG 2ft & 4ft						
Operating hours	0	15,000	30,000	45,000	60,000	100,000
Lumen maintenance factor	1	0.97	0.95	0.93	0.91	0.86
IBGN						
Operating hours	0	15,000	30,000	45,000	60,000	100,000
Lumen maintenance factor	1	0.97	0.93	0.90	0.87	0.81

EMERGENCY LUMENS (5000K 70CRI)

Fixture	IBG			IBGN
Lumen package	8000LM (PS1050 only)	12000LM - 15000LM	18000LM - 60000LM	18000LM - 36000LM
PS1050/PS10250	1600	1300	1900	1200
PS30250	N/A	4000	2400	3800

LUMENS VS. AMBIENT TEMPERATURE

Ambient °C	Ambient °F	Lumen Multiplier
0	32	1.04
5	41	1.03
10	50	1.02
20	68	1.01
25	77	1.00
30	86	0.99
35	95	0.99
40	104	0.98
45	113	0.97
50	122	0.96
55	131	0.96

AMBIENT TEMPERATURE RATINGS

Mounting	Suspended	Surface
Standard temperature rating	113°F (45°C)	95°F (35°C)
HA option temperature rating	131°F (55°C)	113°F (45°C)

LSXR - Fixture Mount Occupancy Sensor (see www.AcuityControls.com for additional information)

- Three interchangeable lens options to satisfy multiple mounting heights and coverage pattern requirements.
- Integrated mounting bracket drops lens down 3" from chase nipple.
- Single or dual relay versions — designed with robust protection from the harsh switching requirements of T5 and LED loads.
- Photocell and 0-10VDC dimming options.
- No PIR field calibration or sensitivity adjustments required.
- Sensor ambient temperature rating of 14°F (-10°C) to 131°F (55°C).

LSXR configuration	Comparable CMRB sensor	Old style sensor nomenclature
For shortest lead times use one of the following LSXR configurations		
LCOZU	CMRB 50	MSI
LCHOSZU	CMRB 50 D	MSID
LCPZU	CMRB 50 P	MSIPED
LAOZU	CMRB 6	MSI360
LAHOSZU	CMRB 6 D	MSI360D
LAPZU	CMRB 6 P	MSI360PED

