

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** [1301410015](#)  
**Status:** **Active**  
**Overview:** [Heavy-Duty Industrial Wiring Devices](#)  
**Description:** Super-Safeway® Plug, 2 Pole/3 Wire, NEMA 5-15, 125V

**Documents:**

[RoHS Certificate of Compliance \(PDF\)](#) [Product Literature \(PDF\)](#)

**Agency Certification**

CSA LR6837  
UL E10176

**General**

Product Family Wiring Devices  
Series [130141](#)  
Catalog Page [http://issuu.com/molex/docs/woodhead\\_product\\_catalog987650-7737/175](http://issuu.com/molex/docs/woodhead_product_catalog987650-7737/175)  
IP Rating N/A  
NEMA Configuration NEMA 5-15  
Overview [Heavy-Duty Industrial Wiring Devices](#)  
Product Literature Order No 987650-8068  
Product Name Super-Safeway™  
Receptacle Type N/A  
Specialty N/A  
Type Plug  
UPC 78678870102  
Woodhead Yes

**Physical**

Cord Grip Body Size N/A  
Flange No  
Flip Lid No  
Gender Female  
Length N/A  
Locking Blade No  
Poles 2-pole/3-wire

**Electrical**

Cord Type N/A  
Current - Maximum per Contact 15.0A  
GFCI No  
Lighted Connector No  
Voltage - Maximum 125V

**Material Info**

Old Part Number 1447



Series image - Reference only

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Contains SVHC(2014 December 17): No

**Halogen-Free**

**Status**

**Low-Halogen**

**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

ELV

Green Image


Not Relevant

**Search Parts in this Series**

[130141](#) Series

# Industrial Duty Wiring Devices Straight Blade 15A 125V 2-Pole/3-Wire NEMA 5-15

Wiring Devices



## Features and Benefits

- NEoTEX® Paracril OZO rubber body yields the best performance for abrasion, chemical exposure and temperature extremes within the Super-Safeway™ offering
- Rugged nylon bodies within the Safeway® offering provide exceptional durability and performance.
- Color-coded ¼" terminal screws pre-set in open position, ready to wire
- Wire screw terminals are tri-drive to be used with straight blade, Phillips and square-drive screw drivers
- Floating blade construction provides self-alignment, and a better mechanical and electrical connection minimizing wear and heat generation
- Transparent wiring guide to verify all wire strands are in place before securing wire
- Captive, tri-drive head, Stainless Steel, speed screw provides easy assembly and long life
- Two-piece cord-clamp strain relief includes tri-drive screws to firmly secure the cord

## Reference Information

UL File No.: E10176  
CSA File No.: LR6837



## Physical

Plug blades and connector contacts: Nickel-plated Brass  
Super-Safeway Outer Housing: NEoTEX Paracril OZO rubber  
Safeway Outer Housing: Nylon  
Face Screws: Stainless Steel  
Face Insert: Nylon  
Wire Saddle Clamp: Brass  
Cord Clamp Screws: Steel, Zinc-plated  
Plug/Connector Range: .335 to .640"

## Environmental

Operating Temperature: Maximum continuous 75° C, minimum -40° C (no impact)  
Temperature Rise: Maximum 30° C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%.



## Super-Safeway Industrial Rubber Plug and Connector

| Description                              | Plug         |             | Connector    |             | Lighted Plug |             | Lighted Connector     |             |
|------------------------------------------|--------------|-------------|--------------|-------------|--------------|-------------|-----------------------|-------------|
|                                          | Woodhead No. | Order No.   | Woodhead No. | Order No.   | Woodhead No. | Order No.   | Woodhead No.          | Order No.   |
| Yellow rubber                            | 1447         | 130141-0015 | 1547         | 130141-0031 |              |             | 15L47 <sup>2</sup>    | 130141-0040 |
| Black rubber                             | 1447BLK      | 130141-0016 | 1547BLK      | 130141-0032 |              |             | 15L47BLK <sup>2</sup> | 130141-0041 |
| Yellow rubber, ground continuity monitor |              |             |              |             | 1447EZ*      | 130141-0017 | 1547GCM <sup>1</sup>  | 130141-0033 |



## Super-Safeway Industrial Rubber Plug and Connector

| Description                                     | Plug         |             | Lighted Connector  |             |
|-------------------------------------------------|--------------|-------------|--------------------|-------------|
|                                                 | Woodhead No. | Order No.   | Woodhead No.       | Order No.   |
| Hospital duty, black rubber, grommet-style grip | 85000        | 130141-0070 |                    |             |
| Hospital duty, gray rubber, grommet-style grip  |              |             | 85002 <sup>1</sup> | 130141-0071 |

\* Ground Continuity Monitor lights indicating a good ground is present

<sup>1</sup> Light indicates power is present

Find adapters and technical support at the end of this section