


Catalogue No.	Min. Order Qty.	Std. Pkg. Qty.	Gross Weight Ea.	Description
---------------	-----------------	----------------	------------------	-------------



3016FG

12

6

0.6

DECORATIVE LOW-PROFILE GLASS CURVE GU10/MR16 TRIM, WHITE FINISH w FROST GLASS CURVE.



**H99 LINE VOLTAGE HOUSINGS**

**HALO**



H99T

48

6

2.62

Feed-Thru Housing with Thermal Protector. UL Damp Location Listed.



H99RT

48

6

1.83

Remodel Housing with Thermal Protector. UL Damp location listed.



H99ICT

48

6

2.60

Feed-Thru Air-Tite housing with Thermal Protector for use in Insulated Ceilings. Supplied with captive bar hangers for 24" joist spacing. UL Damp location listed. Air-Tite For restricted air-flow requirements.

**H99 LINE VOLTAGE TRIMS**



985GUWHT

24

12

0.92

Gloss White Steel Trim, 5 1/16" O.D. 50W GU10 120V



985GUSC

24

12

0.50

Satin Chrome Steel Trim, 5 1/16" O.D. 50W GU10 120V 30deg Tilt



983GUWHT

24

12

1.00

Gloss White Steel Trim, 5 1/16" O.D. 50W GU10 120V 30deg Tilt



995GUP

24

12

0.50

Gloss White Cast Trim, 5 1/16" O.D. 50W GU10 120V 30deg Tilt



987WHT

24

12

0.50

Gloss White Steel Trim, 5 1/16" O.D. 50W PAR20



987SC,AB

24

12

0.50

Satin Chrome or Antique Brass Steel Trim, 5 1/16" O.D. 50W PAR20, 20deg Tilt



997P

24

12

1.00

Satin White Cast Trim, 5 1/16" O.D. 50W PAR20 20deg Tilt



951PS

12

6

0.57

Shower Light, 5 1/16" O.D.  
H99RT - 50W PAR20/R20/40W A19  
H99ICT - 30W R20/35W PAR20



993P

24

6

0.28

Deep Black Coilex Baffle Trim, 5 1/16" O.D.