BANANA BOXTM

Non-metallic Box, 2-Gang, 35.3 Cu. In., with side bracket

By tradeSELECT Catalogue # 2022R

Non-Metallic Boxes, Devices Boxes, For use with non-metallic sheathed cable, 18 Cu. In., 35.3 Cu. In., 2-gang with side Bracket, 1/2 in. setback, 8 Cable Clamp, Molded from high-strength plastic resin. (50-Pack)

Feature

- Energy efficient vapour barrier flange provides superior energy savings, reduces air leakage through exterior walls and eliminates the need for separate vapour / air barriers
- Preset flange at 1/2" for fast positioning
- Engravings at 5/8" and 1" ensure box placement in accurate and consistent depths, while reducing the installation time
- Superior cubic capacity Additional volume makes termination easier and is excellent for deeper body devices
- Oversized nailing / screw bracket for better reach to mount on stud or joint
- High hammer impact resistant when nailing
- Lightweight
- Bright yellow color helps to locate wires in low light levels

Application

Accommodates wiring devices such as switches and receptacles

General

Bracket Setback 0.50" Colour Yellow

Material Thermoplastic Resin

Number of Gang(s) 2-Gang

Type Non-Metallic Box UPC 805035054390

Wiring System Nonmetallic Sheathed Cable



Dimensions

Cubic Capacity 35.3 Cu. In. (578mL)

 Depth
 2.74 in

 Height
 3.90 in

 Weight
 0.289 lb

 Width
 3.98 in

Certifications and Compliance

Industry Standard(s) cCSAus Certified

CSA Cable Range NMD-90 14/2, 14/3, 12/3, 12/2 or 10/2 UL CABLE RANGE NM-B 10/2

.

Logistics

Carton Quantity 50 Pallet Quantity 2400

Product Assets

3D Product View

