



SKYBOL6-LED

Architectural Bollard



SKYBOL is a Dark Sky friendly architectural bollard designed with a perfect blend of functionality and aesthetic appeal, offering selectable features that make it the ideal choice for both commercial and residential application, walkways and outdoor spaces for landscape enhancement.

IDEAL APPLICATIONS

- ✓ Pathways

✓ Townhouses

✓ Condos
- ✓ Campuses


✓ Parkettes

✓ Shopping Malls

SPECIFICATIONS

PERFORMANCE						CONSTRUCTION		
Light Output	3200/2700/1900 lm (Lumen Selectable)					Housing	Extruded aluminum shaft, Die cast base	
Efficacy	139 lm/W					Lens	Polycarbonate	
CCT	3000/4000/5000K (CCT Selectable)					Paint	Corrosion resistant polyester powder coating. Salt Spray tested for 1000 hours	
Beam Distribution	Type V - 360 Degree					Height	42.3"	
LED Lifetime (L80)	>100,000 Hrs					Shaft Diameter	6.3"	
CRI	76					Bolt Circle Diameter	3.94"	
BUG Rating	B1-U1-G1					Weight	15.1 lbs	
ELECTRICAL						CERTIFICATIONS		
Wattage	24/19/14W					cULus Listed for Canada and USA, per UL 1598, CSA C22.2 No. 250.0		
Voltage	120-347V					IK10, IP65, DLC Premium		
Surge Protection	4kV (Built-in Driver) as per ANSI/C82.77-5-207					CONTROLS		
Power Factor	>0.99					0-10V Dimming (5%-100%)		
THD	<8%					DC Dusk to Dawn Photocell		
AMBIENT OPERATING TEMPERATURE						LUMEN MAINTENANCE		
-40°C to 50°C						L90	L80	L70
MAX AMPERAGE DRAW (A)						54,000 Hrs	120,000 Hrs	185,000 Hrs
	120V	208V	240V	277V	347V	Life hours are derived from IESNA LM-80 testing report and projected per IESNA TM-21 calculations.		
SKYBOL6-LED24A14	0.210	0.121	0.105	0.091	0.073			

DARK SKY FRIENDLY



Designed to reduce uplight for Dark Sky Friendly application



Standard photocell for Dusk to Dawn operation



ORDERING GUIDE

SKYBOL6	LED24A14	H	VK	T5		DIM	PC
---------	----------	---	----	----	--	-----	----

Fixture	Wattage	Voltage	Colour Temp.	Beam Distribution	Finish	Dimming	Controls
	Max 24W Min 14W	H - 120-347V	VK - Colour Selectable (3000K/ 4000K/ 5000K)	T5- 360 Degree	BRZ - Bronze* SBK - Sandtex Black CST - Custom finish	DIM - 0-10V Dimming	PC - Photocell

Default Setting: 24W, 4000K, Photocell ON

STOCK CODE

081984 SKYBOL6-LED24A14-H-VK-T5-BRZ-DIM-PC

INCLUDED IN THE BOX




TEMPLATE



ANCHOR BOLT SET (x3)

DIMENSIONS



PHOTOMETRIC PLOTS

