Safety switch, general duty, fusible, 30A, 2 pole, 7.5hp, 240VAC, NEMA 3R, bolt on provision, neutral factory installed





#### Main

Product	Single Throw Safety Switch
Duty Rating	General duty
Device Application	Residential
Disconnect Type	Fusible disconnect switch
Factory Installed Neutral	Neutral (factory installed)
Phase	3 phase
Number of Poles	2
Current Rating	30 A
Voltage Rating	240 V AC
Enclosure Rating NEMA	NEMA 3R
Motor power hp	1.5 Hp at 240 V AC 60 Hz for 1 phase motors 3 Hp at 240 V AC 60 Hz for 3 phase motors 3 Hp at 240 V AC 60 Hz for 1 phase motors 7.5 hp at 240 V AC 60 Hz for 3 phase motors

# Complementary

Short Circuit Current Rating	100 kA maximum depending on fuse H, K or R
Fuse type	H, K or R
Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	3-wire
Wire Size	AWG 14AWG 6 copper AWG 12AWG 6 aluminium
Tightening torque	30 lbf.in (3.39 N.m) 0.000.02 in² (2.0813.3 mm²) (AWG 14AWG 6)
Depth	3.63 in (92.20 mm)
Width	7.25 in (184.15 mm)
Height	9.25 in (234.95 mm)
Net Weight	16.98 lb(US) (7.7 kg)

# **Environment**

#### Ordering and shipping details

Category	00106-D & DU SW,NEMA3R, 30-200A
Discount Schedule	DE1A
GTIN	785901460589
Returnability	Yes
Country of origin	MX

# **Packing Units**

PCE	
1	
5.30 in (13.462 cm)	
7.80 in (19.812 cm)	
10.00 in (25.4 cm)	
	1 5.30 in (13.462 cm) 7.80 in (19.812 cm)

Package 1 Weight	4.75 lb(US) (2.155 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	150
Package 2 Height	40.00 in (101.6 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	767.00 lb(US) (347.905 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	5
Package 3 Height	10.60 in (26.924 cm)
Package 3 Width	23.70 in (60.198 cm)
Package 3 Length	10.20 in (25.908 cm)
Package 3 Weight	25.10 lb(US) (11.385 kg)

# Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes

# Contractual warranty

Warranty	18 months