

APC Back-UPS Pro, 1500VA/900W, Tower, 120V, 10x NEMA 5-15R outlets, AVR, USB Type A + C ports, LCD, User Replaceable Battery

BR1500MS2

Overview

Lead time	Usually in Stock
Main	
Main Input Voltage	120 V
Main Output Voltage	120 V
Rated power in W	900 W
Rated power in VA	1500 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA 5-15P
output connection type	6 NEMA 5-15R 4 NEMA 5-15R surge
Cable length	6 ft (1.8 m)
Number of cables	1
Battery type	Lead-acid battery
Range of product	Back-UPS Pro

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	16 h
Number of battery replacement quantity	1
Battery charger power	16 W rated
Battery design life	35 year(s)
Extended runtime	0
Replacement battery	APCRBC163 ☐

General

Provided equipment coaxial cable user manual USB cable

product web sub-family	Gaming performance
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black aluminium
Height	10.24 in (26 cm)
Width	3.94 in (10 cm)
Depth	14.49 in (36.8 cm)
Net weight	27.6 lb(US) (12.5 kg)
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	60 Hz +/- 3 Hz
Plug standard	NEMA 5-15P
Input voltage limits	88147 V
Maximum input current	12 A

Output

Maximum configurable power in W	900 W
Output frequency	60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Sine wave
Maximum configurable power in VA	1500 VA
Transfer time	8 ms typical : 10 ms maximum

Conformance

Product certifications	ENERGY STAR V2.0 (USA) NOM TUV C-US certified
Equipment protection policy	Lifetime : \$500000

Environmental

Ambient air temperature for operation	32104 °F (040 °C)
Relative humidity	095 % non-condensing
Operating altitude	03000 ft
Ambient air temperature for storage	5104 °F (-1540 °C)
Storage Relative Humidity	095 % non-condensing

Storage altitude	05000 ft (0.00000000001524.0000000000 m)
Acoustic level	45 dBA

Communications & Management

control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

•	•
Surge energy rate	1080 J
Noise suppression	Full time multi-pole noise filtering : 5% of IEEE surge let-through : zero clamping response time: instantaneous
Data line protection	Coaxial cable for CATV/SATV/modem/audio-video

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.12 in (35.87 cm)
Package 1 Width	18.98 in (48.2 cm)
Package 1 Length	8.78 in (22.3 cm)
Package 1 Weight	31.3 lb(US) (14.2 kg)
SCC14	10731304426100

Contractual warranty

Warranty 3 year repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

Environmental Disclosure Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	50414655-abe7-48e2-9b8c-578e40cce4a8
China RoHS Regulation	China RoHS declaration
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No