

**MF 10/5 MM WS****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**MultiMark MultiFit**

For connectors from competitors.

The elastic surface finish makes for simple installation.

This special material enables the strips to be stretched to accommodate slight variations in spacing, especially with long terminal blocks.

A print resolution of 300 dpi also produces a very legible script.

**Your benefits with MultiMark**

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence
- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

]

- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

**General ordering data**

| Version            | Terminal marker, 10 x 5 mm, white                     |
|--------------------|-------------------------------------------------------|
| Order No.          | <a href="#">2519170000</a>                            |
| Type               | MF 10/5 MM WS                                         |
| GTIN (EAN)         | 4050118531190                                         |
| Qty.               | 600 pièce(s)                                          |
| compatible printer | <a href="#">2599430000</a> <a href="#">2599440000</a> |

- Firm hold and durable printing
- Continuous strips save installation time

**MF 10/5 MM WS****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Caractéristiques techniques****Dimensions and weights**

|            |        |                 |            |
|------------|--------|-----------------|------------|
| Depth      | 0,7 mm | Depth (inches)  | 0,028 inch |
| Height     | 10 mm  | Height (inches) | 0,394 inch |
| Width      | 5 mm   | Width (inches)  | 0,197 inch |
| Net weight | 0,1 g  |                 |            |

**Temperatures**

|                             |             |
|-----------------------------|-------------|
| Operating temperature range | -50...90 °C |
|-----------------------------|-------------|

**General data**

|                                   |              |                                   |             |
|-----------------------------------|--------------|-----------------------------------|-------------|
| Colour                            | white        | Halogen                           | No          |
| Material                          | PC-ABS, TPU  | Operating temperature range       | -50...90 °C |
| Operating temperature range, max. | 90 °C        | Operating temperature range, min. | -50 °C      |
| Printed characters                | neutral      | UL 94 flammability rating         | V-2         |
| Version                           | halogen-free | Width                             | 5 mm        |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000761    | ETIM 7.0    | EC000761    |
| ETIM 8.0    | EC000761    | ETIM 9.0    | EC000761    |
| ECLASS 9.0  | 27-14-11-37 | ECLASS 9.1  | 27-14-11-37 |
| ECLASS 10.0 | 27-14-11-37 | ECLASS 11.0 | 27-28-11-01 |
| ECLASS 12.0 | 27-28-11-01 | ECLASS 13.0 | 27-28-11-01 |
| ECLASS 14.0 | 27-28-11-01 |             |             |

**Environmental Product Compliance**

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |                                          |
|------------------|------------------------------------------|
| Engineering Data | <a href="#">CAD data – STEP</a>          |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |

### MF 10/5 MM WS

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Dessins

### Example of use

