



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Multi-directional head
Product compatibility	XCKP XCKT XCMD XCKD
Associated body	ZCT27N12 ZCD28 ZCP37 ZCMD29L5 ZCMD39L2 ZCT21N12 ZCP25 ZCMD37L1 ZCMD29C12 ZCT21G11 ZCMD21L1 ZCMD29L1 ZCT26N12 ZCD31 ZCMD37L2 ZCMD21C12 ZCT27P16 ZCD35 ZCMD21L5 ZCD29 ZCMD25L2 ZCMD81L1 ZCMD29L2 ZCP27 ZCT28G11 ZCMD39L1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

ZCP28
 ZCT27G11
 ZCMD21L2
 ZCP29M12
 ZCMD21M12
 ZCP35
 ZCT21P16
 ZCT25N12
 ZCMD41L2
 ZCMD81L2
 ZCD25
 ZCP31
 ZCMD21L08R12
 ZCP21
 ZCD27
 ZCD37
 ZCP39
 ZCMD25L5
 ZCMD37L5
 ZCT25G11
 ZCD26
 ZCP21M12
 ZCMD61M12
 ZCT28P16
 ZCT25P16
 ZCD39
 ZCD21
 ZCT28N12
 ZCP29
 ZCMD61C12
 ZCMD41L5
 ZCMD81L5
 ZCMD25L1
 ZCT26G11
 ZCMD39L5
 ZCD21M12
 ZCT26P16
 ZCMD21L08U78
 ZCD29M12
 ZCMD41L1
 ZCP26
 ZCMD69C12

Movement of operating head	Multi-directional
Type of operator	Spring rod spring return metal with nitrile boot and thermoplastic end)
Type of approach	Multi-directional approach

Complementary

Switch actuation	By any moving part
Positive opening	Without

Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.04 lb(US) (0.019 kg)
Package 1 Height	0.160 dm
Package 1 width	1.260 dm
Package 1 Length	0.160 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------