



### Main

|                              |   |
|------------------------------|---|
| Ampere Rating                | 20A   |
| Approvals                    | UL Listed - CSA Certified   |
| Catalog Reference Number     | 0730CT9801  |
| Circuit Breaker Type         | Standard  |
| Depth                        | 2.91 Inches   |
| Features                     | VISI-TRIP trip indication   |
| For Use With                 | QO Load Centers, NQOD Panelboards/Interiors and Speed-D switchboard distribution panels |
| General Application          | Provides overload and short circuit protection  |
| HACR Rated                   | Yes   |
| Height                       | 3.00 Inches   |
| Mounting Type                | Plug-On   |
| Number of Poles              | 2-Pole  |
| Phase                        | 1-Phase   |
| Short Circuit Current Rating | 10kA  |
| Space Required               | 2   |
| Terminal Type                | Pressure Plate  |
| Type                         | QO  |
| Voltage Rating               | 120/240VAC  |
| Width                        | 1.50 Inches   |
| Wire Size                    | #14-8 AWG(Al/Cu)  |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.