



Main

Range of Product	Homeline
Product or Component Type	Load Center
Line Rated Current	100 A
[Ue] rated operational voltage	120/240 V AC
Mounting Mode	Wall mount
Short-circuit current	10 kA

Complementary

Electrical Connection	Lugs
AWG gauge	AWG 8...AWG 1 aluminium/copper
Load center type	Main lugs
Number of spaces	6
Number of circuits	12
Number of tandem circuit breakers	6
Phase	1 phase
Cover type	Surface cover
Device Composition	Grounding bar (factory installed)
Wiring configuration	3-wire
Material	Tin plated aluminium: busbar
Enclosure Material	Welded sheet steel
Cover colour	Grey baked enamel
Box number	2R

Environment

Product Certifications	CSA
NEMA degree of protection	NEMA 3R indoor/outdoor)
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)

Ordering and shipping details

Category	00199-DE5 MISC. SERVICE PARTS
Discount Schedule	DE5
GTIN	785901677260
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.88 in (12.4 cm)
Package 1 Width	10.31 in (26.2 cm)
Package 1 Length	14.09 in (35.8 cm)
Package 1 Weight	9.70 lb(US) (4.4 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations