8702SEO2V02S

NEMA Contactor, Type S, reversing, horizontal, Size 3, 90A, 50HP at 575VAC, 3 phase, up to 100kA, 3 pole, 120VAC coil, open style



Main

Product Type	Contactor
Product Range	Type S
Contactor Type	Reversing

Complementary

Complementary		
NEMA Size	3	
Rated Current	90 A	
Number of Poles	3P	
Mounting Orientation	Horizontal	
Wiring Mode	3 wires	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Horsepower Rating	25 HP 200 V AC 30 HP 230 V AC 50 HP 460 V AC 50 HP 575 V AC	
SCCR	Circuit-breaker 150 A maximum, SCCR: 100 kA at 480 V AC Fuse J 200 A maximum, SCCR: 100 kA at 600 V AC Fuse T 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 200 A maximum, SCCR: 100 kA at 600 V AC	
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz	
Control Circuit Type	Separate control circuit	
Control Units	No control units	
Pilot Light	No indicator	
Other Equipment	Fuse not supplied	
Terminal Type	Screw clamp terminals	
Height	7.97 in (202.44 mm)	
Width	12.72 in (323.09 mm)	
Depth	7.00 in (177.80 mm)	

Environment

Enclosure Type	Not rated (open device)	
Certifications	UL Listed[RETURN]CSA	

Ordering and shipping details

Category	21273-8702,36 SE,SF(NOT S*R,T,W)	
Discount Schedule	CP1	
GTIN	785901808916	
Returnability	No	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.60 in (26.924 cm)
Package 1 Width	17.80 in (45.212 cm)
Package 1 Length	26.80 in (68.072 cm)
Package 1 Weight	17.00 lb(US) (7.711 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	[™] China RoHS Declaration

Contractual warranty

Warranty	18 months
vvarianty	10 111011115
•	