

Main

Ampere Rating	200mA
Approvals	UL Listed File Number: E164869 CCN NRKH - CSA Certified File Number: CR44087 Class 3211 03 - CE Marked
Body Type	Tubular - Metal (Shielded) - Short Length - Thread- ed Case
Connection Type	Cable (2m)
Enclosure Material	Nickel Plated Brass
Enclosure Rating	NEMA 3/4X/6P/12/13 - IP67
LED Indicator	360 Degree ring LED shows output status
Maximum Operating Frequency	1000Hz
Maximum Voltage Rat- ing	38VDC
Nominal Sensing Dis- tance	10mm
Operating Temperature Range	-13 to 158 Degrees F (-25 to 70 Degrees C)
Output	DC 3-Wire (PNP) - 1 N.O.
Sensor Diameter	18mm
Supply Voltage	12/24VDC
Type	XS

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.