

**FM160-LED**

DESIGNER SERIES FLUSH MOUNT



NAME:

TYPE:

DATE:

NOTES:

**SPECIFICATIONS**

WIRING:	Installs easily in traditional junction boxes ( 3" or 4" ).
HOUSING DETAILS:	This flush mount unit uses metal housing. The Azure 12" is available with or without the motion sensor. The motion sensor is a microwave sensor with a range up to 15 feet (4.5m), and a time delay of 5 minutes. Sensing no movement within that time period, the light will shut off automatically.
OPTICS:	LED technology delivers 1500 lumens (12" version ) and 2000 lumens (16" version).
ELECTRICAL:	Integrated LEDs are direct-AC with no external driver. For usage in interior ceiling or wall installations in residential or commercial applications.  Ambient operating temperature: -40°C (-40°F) to +50°C (+122°F).  Certifications: ETL and Energy Star listed to U.S. and Canadian safety standards, as well as DAMP LOCATIONS rated.
LENS:	White decorative acrylic frosted lens provides an even light distribution.

COLOR TEMPERATURE:	3K - 4K
OPERATING TEMPERATURE:	-20°C + 50°C
CRI:	80+
LUMEN OUTPUT:	2000 lumens
DIMMABLE:	Yes
WATTS:	23W
LED LIFE:	50,000 hours
WARRANTY:	5 years
VOLTAGE:	120V
DIAMETER:	16" (406.4mm)
HEIGHT:	3.75" (95.3mm)
INTEGRATED MOTION SENSOR:	No


**APPLICATIONS**

The Azure series of LED flush mount fixtures by NDR offers an affordable and stylish design that will complement a varied assortment of lighting applications. The acrylic diffuser may be easily removed for installation and cleaning. Ideal for interior ceiling or wall installations in residential or commercial applications.

**FM160-LED**

DESIGNER SERIES FLUSH MOUNT

## DIMENSIONS



## RATINGS



## ORDERING GUIDE

**AZURE FM160 SERIES**

Series	Color Temperature	Finish
FM160-23W	3K 3000K/80CRI/23W	WH White
	4K 4000K/80CRI/23W	
Notes:	Configure product using <b>BOLD</b> options: Ex: <b>FM160-23W-3K-WH</b>	