

Industrial grade straight blade devices

Product description


2-pole, 3-wire grounding
15A, 125V/AC
NEMA 5-15



5-15P



5-15R



AH5266



AH5969BK



AH5278C



AH5278

Industrial grade plugs & connectors



Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
15	125	5-15	Ultra grip straight body	0.33-0.66" (8.3-16.7mm)	BK & W	□ AH5266	□ AH5269	•	•
			Ultra grip straight body	0.33-0.66" (8.3-16.7mm)	BK	□ AH5266BK	□ AH5269BK	•	•
			Safety grip angled body	0.33-0.66" (8.3-16.7mm)	BK & W	□ AH5266A	—	•	•
			Quick grip straight body	0.22-0.66" (5.6-16.7mm)	BK	□ AH5965BK	□ AH5969BK	•	
			Quick grip straight body	0.22-0.66" (5.6-16.7mm)	Y	□ AH5965Y	□ AH5969Y	•	
			Auto grip straight body	0.33-0.66" (8.3-16.7mm)	BK & W	□ 5266N	□ 5269N	•	•

Industrial grade flanged inlets & outlets



Rating A	V/AC	NEMA	Description	Color	Inlet catalog no.	Outlet catalog no.	
15	125	5-15	Nylon construction, back wire	BK & W	□ AH5278C [†]	□ AH5279C [*]	•
			Metal shell, back wire	Steel	□ AH5278 ^Δ	□ AH5246	•

* UL and CSA Listed, [†] Fed Spec certified, ^ΔOnly NOM spec

Industrial grade dimensional
Information: B-16, B-17

Specification information:

Safety grip industrial plugs & connectors: B-24
Quick grip plugs & connectors: B-24
Auto grip industrial plugs & connectors: B-24
Industrial flanged inlets & Flanged outlets: B-25

Color information:

BK (Black), W (White), Y (Yellow)



Compliances, specifications and availability are subject to change without notice.



Indicates NAFTA compliant - Page Q-32



RoHS compliant - Page Q-32