

A

PVC Insulated Terminals & Connectors (Professional Series)

Insulated terminals and connectors feature a rigid insulation sleeve of polyvinyl chloride (PVC). Sleeves are permanently affixed to the conductive barrel, providing quick crimping. The tough plastic sleeve protects against vibration damage by preventing wire flex at the crimp point. Operating temperatures: -55°C to 90°C. 600 Volt rating. Crimp tools can be found on pages 42-45

PVC Insulated Ring Terminals (Professional Series)

22-18GA



Stud Size 4-6
761000 100 pk
761000M 1000 pk



Stud Size 8-10
761003 100 pk
761003M 1000 pk



Stud Size 12-1/4"
761004 100 pk
761004M 1000 pk



Stud Size 5/16"-3/8"
761006 100 pk

16-14GA



Stud Size 4-6
761016 100 pk
761016M 1000 pk



Stud Size 6-8
761018 100 pk
761018M 1000 pk



Stud Size 8-10
761019 100 pk
761019M 1000 pk



Stud Size 12-1/4"
761020 100 pk
761020M 1000 pk



Stud Size 5/16"-3/8"
761022 50 pk
761022M 1000 pk

12-10GA



Stud Size 4-6
761032 50 pk



Stud Size 8-10
761034 50 pk
761034M 1000 pk



Stud Size 12-1/4"
761035 50 pk
761035M 1000 pk



Stud Size 5/16"-3/8"
761037 50 pk
761037M 1000 pk



Stud Size 7/16"-1/2"
761038 25 pk
761038M 1000 pk

8GA



Stud Size #10
761603 25 pk
761603M 1000 pk



Stud Size 1/4"
761600 25 pk



Stud Size 5/16"
761602 25 pk
761602M 1000 pk



Stud Size 3/8"
761601 25 pk



Stud Size 1/2"
761604 25 pk
761604M 1000 pk

6GA



Stud Size #10
761605 25 pk
761605M 1000 pk



Stud Size 1/4"
761610 25 pk
761610M 1000 pk



Stud Size 5/16"
761612 25 pk
761612M 1000 pk



Stud Size 3/8"
761611 25 pk



Stud Size 1/2"
761023 25 pk
761023M 1000 pk