

YDS25AT, Aluminum Full Tension Sleeve Splice

By Burndy Catalog # YDS25AT

Aluminium Hysplice, 7-1/4 in L, Full Tension Sleeve for All Aluminum Compressed and Compact Conductors, Die index:243.

Features

- Full-Tension sleeve made of aluminum tubing with staked-in cable stop
- Sizes 1/0 and larger feature a taper for gradual transition of stress
- Pre-Filled with PENETROX Joint Compound and Capped

Application

For All Aluminum Compressed And Compact Conductors

General

Catalog Number YDS25AT
Color Code Yellow
Connector Type Splice
Die Index BG or 243
EU RoHS Indicator Yes
Insulation Y
Material Aluminum

Plated N

Plating Type Unplated

Prefilled Oxide Inhibitor

 Sub Brand
 HYSPLICE

 Trade Name
 HYSPLICE™

 Type
 YDS-AT

 UPC
 781810820971

 UPC 12 Digit
 7818108209711

Dimensions

Dimension - B Length fraction 3-53/93 in Dimension - B Length inch 3.57 in Dimension - L Length Overall 185 mm

mm

Dimension - Length Overall 7.27 in

inch



Dimension - Outside Diameter 0.62 in

inch

Conductor Related

Conductor - ACSR Cmpt Size 1/0 AWG Conductor - ACSR Cmpt Size 1/0 AWG

Range

Conductor - AL Str Size 1/0 AWG Conductor - AL Str Size Range 1/0 AWG

Conductor Type

• ACSR C Str-Size
• AL C Str-Size

Certifications And Compliance

Buy American Compliant Contact Manufacturer
Certification - CSA Approved No
Certification - ETL No
Certification - UL Recognized No
Certification - cULus No
Standards - RoHS Compliance CM
Status
UL Listed No

Logistics

Carton Quantity 25
Minimum Pack Quantity 1
Pallet Quantity 9800

Product Assets

Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_YDS-AT_LineArt

Sales Drawings - SD..021880-01 Specifications - YDS25AT

