NSYCVF85M115PF

ClimaSys forced vent. IP54, 85m3/h, 115V, with outlet grille and filter G2





Main

Range	ClimaSys
Product name	ClimaSys CV
Product or Component Type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter: 20869.97 Gal/ hr(US) (79 m3/h) at 50 Hz Free flow rate with standard filter: 24304.26 Gal/ hr(US) (92 m3/h) at 60 Hz
[Us] rated supply voltage	75126 V
Input voltage	115 V 50/60 Hz

Complementary

1	
Absorbed power	15 W 60 Hz 16 W 50 Hz
Line Rated Current	0.207 A 50 Hz 0.179 A 60 Hz
Noise level < at	4649 dB
Bearing type	Ball
Height	External 6.69 in (170 mm)
Width	External 5.91 in (150 mm)
Depth	External 2.44 in (62 mm)
Cut-out dimensions	125 x 125 mm
Net Weight	1.72 lb(US) (0.78 kg)
Material	Outlet grille injected thermoplastic (ASA PC)
Color	Outlet grille Gray RAL 7035)
Ambient Air Temperature for Operation	-4140 °F (-2060 °C)
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Maximum pressure	50 Pa flow rate 0 m³/h
Connections - Terminals	Faston connector
IP degree of protection	IP54
Device composition	axial motor protective grille on the front and rear surfaces filter front of axial motor outlet grille front cut-out template power cord
Condition of use	Overfrequent filter replacement should be avoided Surrounding environment must be relatively clean Outside temperature must be 5 °C lower than inside temperature Flow rates depends on the work point, see ProClima software Filter must be cleaned and replaced regularly

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480151217
Returnability	Yes
Country of origin	FR

Packing Units

PCE
1
3.35 in (8.5 cm)
6.10 in (15.5 cm)
7.28 in (18.5 cm)
32.28 oz (915 g)
CAR
10
8.27 in (21 cm)
12.99 in (33 cm)
16.93 in (43 cm)
21.00 lb(US) (9.526 kg)
PAM
240
41.34 in (105 cm)
39.37 in (100 cm)
47.24 in (120 cm)
533.52 lb(US) (242 kg)

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	

Contractual warranty

Warranty	18 months	