

YC28C2, Copper C-Shape Connector

By Burndy Catalog # YC28C2

CU Compression C Shape Compression Connector, 600 Volts to 35 Kv, Run: 3/0 Str. - 4/0 Str., Tap: 6 Sol. - 2 Str.



- Range-taking connector lowering inventory requirements
- Compact size, easy to tape and insulate connection
- High conductivity wrought copper provides low resistance and excellent electrical conductivity

Application

For Making Tap Or Parallel Copper Connections

General

Catalog Number YC28C2 Die Index F or D3 EU RoHS Indicator Yes Material Copper Plated Ν Plating Type Unplated **CRIMPIT** Sub Brand Trade Name CRIMPIT™ YC-C Series Type UPC 781810115756 UPC 12 Digit 7818101157566

Dimensions

Dimension - Height inch 1.65 in Dimension - Height mm 0 mm Dimension - L Length Overall 27 mm

Dimension - Length Overall 1.07 in

inch

Conductor Related

Conductor - Copper Str Run

Range

Conductor - Copper Str Tap

Range

3/0 AWG-4/0 AWG

6 Sol. - 2 Str



Conductor Type

Cu C Sol-Size

Certifications And Compliance

Buy American Compliant Contact Manufacturer

Certification - CSA Approved Certification - ETL No Certification - UL Recognized No Certification - cULus

Certified Listed Buy America Compliant (All

status valid till December

2024)

Industry Standard(s) UL 486A

UL486B

UL 486A;UL486B

Standards - Industry Standards

Standards - RoHS Compliance

Status

UL Listed Yes

Logistics

25 Carton Quantity Minimum Pack Quantity Pallet Quantity 5800

Product Assets

3D Models - YC28C2 MODEL-PDF

3D Models - YC28C2 MODEL-STEP

3D Models - YC28C2 MODEL-IGES

Catalogs - BURNDY Master Catalog - Section H - Overhead

Distribution

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

Product Cross Section Image(s) - BUR_YCC_Lineart

Sales Drawings - SE..090670-01

Specifications - YC28C2

