

Kellems Wire Management,
Liquidtight System, Straight, 1",
Non-Insulated with Mesh

By Hubbell Wiring Device-Kellems
Catalog # 074093404

Kellems Wire Management, Liquidtight System, Straight, 1", Non-
Insulated with Mesh

Application

- 1" NPT

Performance

- Environmental - Flammability - UL 94-HB and UL 94-V2
- Environmental - Hazardous Location - Suitable for use in hazardous locations per Class I, Div. 2, Class II, Div. 1 & 2, Class III, Div. 1 & 2
- Environmental - Operating Temperature - -30°F to +225°F (-34°C to +107°C)

General

Catalog Number	074093404
Material	Steel Fitting, Stainless Steel Mesh
Series	Liquidtight Conduit
Style	For Metal & Non-Metallic PolyTuff I



Type	Straight With Male Fitting
UPC	783585331638

Dimensions

Conduit Trade Size	1 in
--------------------	------

Certifications And Compliance

Industry Standard(s)	UL Listed
----------------------	-----------

Logistics

Carton Quantity	10
-----------------	----

Product Assets

- [Catalogs - WDK Catalog Full 2024](#)
- [Literature - Wire Management Solutions Brochure](#)
- [Specifications - 74093404](#)
- [Warranty - Industrial & Commercial Products](#)