



Representative

Catalog Number: LSC1250W2LD10
Product ID: 7TBA133180R0842
UPC Number: 62461630332
Status: Active

Pictogram Combination Unit, single face, Battery Type: lead-calcium, Voltage DC: 12V, Battery Wattage: 50W, self-powered, Colour: factory white, two lamps, Lamp Type: MR16 LED, Lamp Voltage: 12V, Lamp Wattage: 6W, 120/347VAC, Head Style: standard, Battery Run Time: 30 minutes

Steel Combination Unit Combination Units

- Long-life white LED light sources is warranted for ten (10) years
- Remote load capacity: 80W up to 560 feet of egress illumination when using LED remote heads

North American Specifications (UNSPSC)

UNSPSC	39111707 Combo light unit exit
IGCC	3938 Combo light unit exit
Brand Name	Lumacell
Type	Pictogram Combination Unit
Application	Institutional, Commercial, Hospitality
Standard	CSA
Wattage	50W
Voltage Rating	120/347VAC, 12VDC
Battery Runtime	30 minutes
Battery	Lead-calcium
Lamp Type	MR16 LED
Number Of Lamps	2
Legend	On
Size	13-1/2 Inches Height x 13-3/8 Inches Width
Material	Steel
Mounting	Universal
Color	Factory white
Lamp Wattage	6W

European Specifications (ETIM)

ETIM	EC001957 Emergency luminaire
Lamp type	LED exchangeable
Lamp power	6W
Material housing	Steel
Colour housing	White
Battery quality	Lead
Voltage type	AC/DC
Nominal voltage	120-347V
Width	340mm
Height/depth	342mm

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	9 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet Canada Available on Website

For further technical assistance, please contact us...

Thomas & Betts Canada
700, Thomas Avenue
Saint-Jean-sur-Richelieu, QC
J2X 2M9
www.tnb.ca

T&B Technical Support
<http://www.tnb.ca/en/contactus/?id=ALL>

Hours: 7h00 - 18h00
Monday-Friday