

Actual

Catalog Number: LT475T-SC

**Product ID:** 7TAA115120R0048 **UPC Number:** 78599108592

Status: Active

Liquidtight Conduit Fitting, 45 Degree Bend, Insulated, Trade Size 3/4 Inch, Malleable Iron

- Typical applications include motor and control, heating and air conditioning, outdoor lighting and transformer connection
- To positively bond conduits to a box or an enclosure indoors and outdoors
- To protect conductors from mechanical damage due to vibration and movement, and seal out cutting oils, coolants, etc.

North American Specifications (UNSPSC)	
UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Brand Name	Steel City
Туре	Connectors-45 Degree
Special Features	Screw in Ferrule and Split Sealing Ring Makes for a Quick Install While Still Providing a Liquidtight Seal that Meets UL Standards
Application	Typical Applications Include Motor and Control, Heating and Air Conditioning, Outdoor Lighting and Transformer Connection
Standard	UL E23018
Size	3/4 Inch
Connection	45 Degree
Material	Malleable Iron
Color	Metallic
Insulation	Yes

European Specifications (ETIM)		
ETIM	EC001180 Screw connection for protective metallic	
	hose	
Nominal size in inch	3/4 inch	
Model	45°-elbow	
Revolving thread	N	
Construction type	External thread	
Material housing	Other	
Surface protection	Untreated	
Thread length	15.0mm	

Packaging	
Inner Quantity	10
Inner Dimensions (inches)	8.2x4.3x3.6
Outer Quantity	50
Outer Dimensions (inches)	21.5x8.8x4.2
Weight Uom	0.42 lbs. Each

## **Documents / Support Tools**

Technical Drawing / Data Sheet WSD-001294

## For further technical assistance, please contact us...

ABB Installation Products Technical Support MS 3B-50

860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com