



### Main

|                               |                                                                                                                             |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Range of product              | 9007                                                                                                                        |
| Series name                   | Heavy duty                                                                                                                  |
| Device short name             | C                                                                                                                           |
| Head type                     | Turret head rotary lever                                                                                                    |
| Type of operator              | Spring return lever arm standard pre-travel) to be ordered separately<br>Drive shaft reduced diameter to 0.306 in)lever arm |
| Switch actuation              | CW                                                                                                                          |
| Cable entry                   | NPT conduit entry 0.5 in (12.70 mm)                                                                                         |
| Contacts type and composition | 2 NO/2 NC                                                                                                                   |
| Contact operation             | Snap action                                                                                                                 |

### Complementary

|                                              |                          |
|----------------------------------------------|--------------------------|
| Body material                                | Zinc alloy               |
| Switch function                              | SPDT-DB                  |
| Contact form                                 | Form ZZ                  |
| Contacts material                            | Silver alloy (Ag/Ni)     |
| Minimum torque for tripping                  | 4 lbf.in (0.45 N.m)      |
| Tripping angle                               | 4 °                      |
| Maximum displacement angle                   | 90 °                     |
| [Ie] rated operational current               | 10 A, A600<br>10 A, Q600 |
| [Ithe] conventional enclosed thermal current | 10 A                     |
| [Ui] rated insulation voltage                | 600 V                    |
| Local signalling                             | Without pilot light      |
| Product certifications                       | CSA<br>CE<br>UL Listed   |
| Provided equipment                           | Receptacle               |

### Environment

|                                       |                            |
|---------------------------------------|----------------------------|
| Ambient air temperature for operation | -20...185 °F (-29...85 °C) |
|---------------------------------------|----------------------------|

### Ordering and shipping details

|                       |                               |
|-----------------------|-------------------------------|
| Category              | 21499 - 9007 C LIMIT SWITCHES |
| Discount Schedule     | DS1                           |
| GTIN                  | 00785901116042                |
| Nbr. of units in pkg. | 1                             |
| Package weight(Lbs)   | 1.25 lb(US) (0.57 kg)         |
| Returnability         | Yes                           |
| Country of origin     | MX                            |

### Packing Units

|                        |                    |
|------------------------|--------------------|
| Unit Type of Package 1 | PCE                |
| Package 1 Height       | 3.00 in (7.62 cm)  |
| Package 1 width        | 4.50 in (11.43 cm) |
| Package 1 Length       | 1.80 in (4.572 cm) |

Offer Sustainability

|                           |                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation          | <a href="#"> REACH Declaration</a>                                                                                                                                                                                                                                                               |
| EU RoHS Directive         | Not applicable, out of EU RoHS legal scope                                                                                                                                                                                                                                                                                                                                        |
| Environmental Disclosure  | <a href="#"> Product Environmental Profile</a>                                                                                                                                                                                                                                                   |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|