8736SCO8V02S

NEMA starter, Type S, reversing, horizontal, Size 1, 27A, 10HP at 575VAC, 5kA SSCR, 3 phase, 3 pole, melting alloy overload, 120VAC coil, open



Main

Product Type	Starter
Product Range	S
Starter Type	Reversing

Complementary

NEMA Size	1	_
Rated Current	27 A	_
Number of Poles	3P	_
Mounting Orientation	Horizontal	_
Wiring Mode	3 wires	-
Maximum Voltage Rating	600 V AC	_
Phase	3 phase	_
Type of Overload	Melting alloy 3	_
Horsepower Rating	7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC	- '
SCCR	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC	-
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz	- :
Control Circuit Type	Separate control circuit	
Control Units	No control units	_
Pilot Light	Without pilot light	_
Auxiliary Contacts	Without	_
Terminal Type	Screw clamp terminals	-
Height	6.91 in (175.51 mm)	_
Width	7.13 in (181.10 mm)	- :
Depth	5.31 in (134.87 mm)	_

Environment

Enclosure Type	Not rated (open device)
Certifications	UL Listed[RETURN]CSA

Ordering and shipping details

Category	21272-8702,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901872726
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.39 in (21.3 cm)
Package 1 Width	8.39 in (21.3 cm)
Package 1 Length	12.20 in (31.0 cm)
Package 1 Weight	9.79 lb(US) (4.44 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
vvarianty	10 111011115
•	