



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	24 V DC
Main Output Voltage	24 V DC
Battery Type	VRLA
Provided Equipment	User Manual

Batteries & Runtime

Battery Placement	Battery Cabinet
Device mounting	DIN rail
Battery Voltage	24 V

Physical

Color	Metal grey
Height	5.08 in (129 mm)
Width	7.56 in (192 mm)
Depth	4.69 in (119 mm)
Net Weight	9.92 lb(US) (4.5 kg)
Mounting preference	No preference
USB compatible	No

Output

Battery Capacity	4.5 Ah
------------------	--------

Conformance

Product Certifications	CE[RETURN]TÜV
Standards	IEC 62368-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental

Ambient Air Temperature for Operation	5...122 °F (-15...50 °C)
Operating altitude	0...9842.52 ft (0...3000 m)
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...158 °F (-15...70 °C)
Storage altitude	0.00...9842.52 ft (0...3000 m)
Storage Relative Humidity	0...95 %

Ordering and shipping details

GTIN	731304451518
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.24 in (234.7 mm)
Package 1 Width	7.48 in (190 mm)
Package 1 Length	7.40 in (188 mm)
Package 1 Weight	10.58 lb(US) (4.8 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	1 Year
----------	--------