

Kellems Wire Management, Deluxe  
Cord Grips, Straight Male, Non-  
Metallic, .500-.625", 3/4" with Mesh

By Hubbell Wiring Device-Kellems  
Catalog # 074011336

Kellems Wire Management, Deluxe Cord Grips, Straight Male,  
Non-Metallic, .500-.625", 3/4" with Mesh

Features

- Aluminum Fitting
- Stainless steel mesh is corrosion resistant
- Neoprene bushing is oil and watertight

Application

Straight Male- Form 3

Performance

- Environmental - Flammability - UL 94HB (Strand grip), UL 94V-2(Fitting)
- Environmental - Hazardous Locations - Suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 N.E.C
- Environmental - Operating Temperatures - -40°F to +225°F (-40°C to +107°C)
- Environmental - Wet Locations - Suitable for use in wet locations when used with a listed sealing ring between box and fitting

General

Catalog Number	074011336
Color	Metallic
Cord Range	.500"-.625" (1.27-1.59)
EU RoHS Indicator	Yes
Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Sealing Ring Between Box And Fitting.
Item Type	Deluxe Cord Grips
Material	Nylon Fittings, Stainless Steel Mesh
Material - Mounting Hardware	Locknut or Tapped Opening
Series	Deluxe Cord Grips
Specifications	<ul style="list-style-type: none"><li>• Body - Nylon</li><li>• Bushing - Neoprene</li><li>• Nut - Nylon</li><li>• Strand - Stainless Steel</li></ul>
Style	For Insulated Cables
Temperature Rating	Minimum -40 Deg F to 225 Deg F (-40 Deg C to 107 Deg C)



Thread Size	3/4" NPT
Type	Straight Male Thread
UPC	783585331072

Dimensions

Dimensions	2.15 in x 1.56 in x 1.56 in
Display Size	3/4" NPT
Height	1.56 in
Length	2.15 in
Weight	0.2 lb
Width	1.56 in

Conductor Related

Cable Diameter Range	0.500 in-0.625 in
Cable Size	.500"-.625" (1.27-1.59)
Number of Conductors	Single

Certifications And Compliance

Industry Standard(s)	UL Listed
Standards - RoHS Compliance	CM
Status	

Logistics

Carton Quantity	5
Pallet Quantity	1620

Product Assets

[Catalog Page - WDK C-12 Catalog Page](#)  
[Catalog Page - WDK W-52 Catalog Page](#)  
[Catalog Page - WDK W-51 Catalog Page](#)  
[Catalog Page - WDK H-15 Catalog Page](#)  
[Catalogs - WDK Catalog Full 2024](#)  
[Installation Manuals - WIRING\\_30920064\\_INSTALLINST](#)  
[Literature - Wire Management Solutions Brochure](#)  
[Literature - FOOD & BEVERAGE SOLUTIONS](#)  
[Literature - PULP & PAPER SOLUTIONS](#)  
[Literature - Pulp & Paper Solutions](#)  
[Literature - FOOD & BEVERAGE SOLUTIONS](#)  
[Sales Drawings - WDK\\_074011336\\_DRAWING\\_PDF](#)  
[Specifications - 74011336 Specification Sheet French](#)  
[Specifications - Wiring 074011336 Specification Sheet](#)



**A Hubbell brand**