8538SBW21V03

NEMA Combination Starter, Type S, nonfusible disconnect, Size 0, 18A, 5 HP at 600 VAC polyphase, 240 VAC coil, NEMA 4/4X



Main

Product	Combination Starter
Туре	S
Control Circuit Type	Common control circuit

Complementary

Complementary		
Control Circuit Voltage	220 V AC 50 Hz 240 V AC 60 Hz	
Starter Type	Non reversing	
Number of Poles	3P	
Horsepower Rating	3 Hp 200 V AC, 3 phase 3 Hp 230 V AC, 3 phase 5 Hp 460 V AC, 3 phase 5 hp 575 V AC, 3 phase	
Maximum Voltage Rating	600 V AC	
Control Units	No control units	
Pilot Light	No indicator	
Auxiliary Contacts	Without	
Thermal overload type	Melting alloy 3	
Disconnect Type	Non-fusible disconnect switch	
NEMA size	0	

Environment

Enclosure Type	NEMA 4X glass polyester with external reset
Lifeloguic Type	NEWA 4X glass polyester with external reset

Ordering and shipping details

Category	21217 - 8538,39 S*R,S*T,S*W
Discount Schedule	CP1
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	40.00 lb(US) (18.144 kg)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------