



## Main

Range	Thalassa
Accessory / separate part category	Fixing accessory
Product or Component Type	Post fixing device
Device Application	Multi-purpose
Enclosure nominal dimensions	- H: 16.93 in (430 mm) W: 12.99 in (330 mm) D: 7.87 in (200 mm)
Mounting Location	Outdoor installations on a post Rear of enclosure
Range compatibility	Thalassa Thalassa PLM
Device composition	Fixing elements 2 support rail 2 strip

## Complementary

Material	Galvanised steel
Fixing mode	By fixing element - on a post
Permanent permissible load	220.46 lb(US) (100 kg)
Height	1.77 in (45 mm)
Width	11.61 in (295 mm)
Depth	1.28 in (32.5 mm)
Diameter	8.46 in (215 mm)

## Ordering and shipping details






Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480192500
Returnability	No
Country of origin	ES

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.77 in (4.5 cm)
Package 1 Width	7.87 in (20.0 cm)
Package 1 Length	12.60 in (32.0 cm)
Package 1 Weight	3.72 lb(US) (1.687 kg)
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	12.60 in (32.0 cm)
Package 2 Width	16.73 in (42.5 cm)
Package 2 Length	3.94 in (10.0 cm)
Package 2 Weight	38.76 lb(US) (17.583 kg)
Unit Type of Package 3	PAM
Number of Units in Package 3	100
Package 3 Height	47.24 in (120 cm)

Package 3 Width	39.37 in (100 cm)
Package 3 Length	35.43 in (90 cm)
Package 3 Weight	727.53 lb(US) (330 kg)

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

### Contractual warranty

Warranty	18 months
----------	-----------