Rittal - The System.

Faster – better – everywhere.

Wallmounted enclosure − WM 8017.541

Date : Feb 5, 2020



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Wallmounted enclosure - WM 8017.541 - WM162008NC

: 05.02.2020 build on www.rittal.com/ca-en



Drod	luct d	escri	ntion
1 100	uct u	COUL	puon

Material: Door: Carbon steel, all-round foamed-in PU seal

Housing: Carbon steel

Surface finish: Housing and door: Dipcoat primed, powder-coated on the outside, textured paint

Mounting plate: Zinc-plated

Color: RAL 7035

Protection category IP to IEC 60 529:

IP 66

Protection category

NEMA:

NEMA 4

Supply includes: Housing with door(s)

Door hinged on left Mounting plate

Rear wall mounting holes

Quarter turn latch with slotted head insert

Product features

Dimensions: Height: 400 mm (16 ")

Width: 500 mm (20 ") Depth: 210 mm (8.3 ")

Material thickness:: Housing: 1.5 mm (0.06 ")

Door: 1.5 mm (0.06 ")

Mounting plate: 1.5 mm (0.06 ")

Mounting plate: Height: 375 mm (15 ")

Width: 449 mm (18 ")

© Rittal 2020

Weight/packaging unit:	10 kg (22 lb.)
Approvals	
Approvals:	UL + C-UL
Declarations:	Declaration of conformity

© Rittal 2020 2