



Main

Product	Hanger
Device Application	Seismic
Range	I-Line

Complementary

Rated Current	3000 A aluminium
Length	22.22 in (564.39 mm)
Width	9.74 in (247.40 mm)

Environment

Standards	UL 857 CSA C22.2 No 27:1994 IEC 61439-6
-----------	---





Ordering and shipping details


Category	20204-HANGERS WITH BILLING
Discount Schedule	PE8
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	12.00 lb(US) (5.443 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	 RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes

Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes

Contractual warranty	
Warranty	18 months