

**NC425-55MED**

NC425-55MED 4.25" PAR16/PAR20 DEEP NC HOUSING - IC / NON-IC



NAME:

TYPE:

DATE:

NOTES:

**SPECIFICATIONS**

VOLTAGE: 120V

**HOUSING DETAILS:** Housing constructed of heavy duty galvanized steel with junction box - Built-in thermal protection.

For use with a PAR20 or MRE26 (PAR16) style bulb, in either a halogen or LED type.

Insulated Ceiling Application; the use of an LED type bulb is required. Refer to trim model for specific bulb wattages

Adjustable mounting bars included, allows for installation between 13.00" (320mm) and 26.00"(660mm) openings. "Quick Connect" wire connectors included. Can be installed in ceilings up to 2.00" (50mm) in thickness. Approved for damp locations

Some municipalities will require the use of a vapor barrier in an insulated application. Verify local building codes prior to installation.

**COMPATIBLE TRIMS:** TR1325 - 4.25" PAR20 SHOWER TRIM  
TR1350 - 4.25" PAR20 GIMBAL TRIM  
TR1510 - 4.25" PAR16 REGRESSED TRIM  
TR1530 - 4.25" PAR16 GIMBAL TRIM

CUTTING HOLE: 4.38" (111.3mm)

WARRANTY: 1 year

HEIGHT: 5.75" (146.1mm)

LENGTH: 8.5" (215.9mm)

WIDTH: 7.0" (177.8mm)


**APPLICATIONS**

Ideal for open ceilings, New Construction or acoustic tiles

**NC425-55MED**

NC425-55MED 4.25" PAR16/PAR20 DEEP NC HOUSING - IC / NON-IC

## DIMENSIONS



## RATINGS



## ORDERING GUIDE

**NC425-MED SERIES**

| Series      | Product                                                             |
|-------------|---------------------------------------------------------------------|
| NC425-55MED | 4.25" Deep New Construction Housing-PAR20 / PAR16                   |
| Notes:      | Configure product using <b>BOLD</b> options: Ex: <b>NC425-55MED</b> |