760236113 | DM24-24LC-WB-ULL



G2 ULL Multimode OM5 MPO-24 Distribution Module, 24LC to 1X24f MPO unpinned, internal shutters

Product Classification

Regional Availability Asia | Australia/New Zealand | EMEA | Latin America | North America

PortfolioCommScope®Product TypeFiber moduleProduct BrandSYSTIMAX ULL

Product Series G2

General Specifications

Color, front Lime green

Color, rear Gray
Interface, front LC

Interface Feature, front Standard

Interface, rear MPO Unpinned

Interface Feature, rear Key up/up

Polarity Method B Enhanced (ULL)

Shuttered Yes
Total Fibers, quantity 24

Dimensions

 Height
 26.42 mm | 1.04 in

 Width
 96.52 mm | 3.8 in

 Depth
 117.35 mm | 4.62 in

Optical Specifications

Fiber Mode Multimode

Fiber Type OM5, LazrSPEED® wideband

Insertion Loss, maximum 0.35 dB



760236113 | DM24-24LC-WB-ULL

Environmental Specifications

Qualification Standards IEC 61753-1 | TIA-568.3-D

Safety Standard CE | CSA | UL

Packaging and Weights

Packaging quantity 1

Weight, net 0.113 kg | 0.249 lb

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant



