# NSYTBP292416H

PC box IP66 IK08 RAL7035 Int.H275W225D160 Ext.H291W241D168 opaque PC cover H60





#### Main

Range	Thalassa	
Product name	Thalassa TBP	
Device Application	Multi-purpose	
Category	Industrial box	
Height	11.46 in (291 mm)	
Width	9.49 in (241 mm)	
Depth	6.61 in (168 mm)	
Internal height	10.83 in (275 mm)	
Internal width	8.86 in (225 mm)	
Internal depth	6.30 in (160 mm)	
Enclosure mounting	Wall mounted	
Device composition	1 body	
	1 cover 4 cover screw	
Body type	One piece moulded	
Type of front cover	High plain cover	
Cover fixing	Plastic screws	
Lock type	Captive screw flat outside sealed area	
Removable parts	Cover by captive screws	

#### Complementary

Material	polycarbonate	
Color	Gray RAL 7035)	
Standards	IEC 62208 UL 508 A	
Product Certifications	TÜV[RETURN]UL	
Electrical Insulation Class	Class II	
Mounting location	Outdoor (with canopy or shelter and anticondensation valve)	
Net Weight	2.73 lb(US) (1.24 kg)	

#### Environment

degree of protection IP66 conforming to NEMA 4.4X	
IK degree of protection	IK08 IEC 62262
Fire resistance	1760 °F (960 °C)
Ambient Air Temperature for Storage	5140 °F (-1560 °C)
Operating temperature	-13176 °F (-2580 °C)

#### Ordering and shipping details

80033-ENCLOSURE SYSTEMS POLYESTER	
ES1	
3606480165757	
Yes	
HU	

## Packing Units

PCE	
1	
7.09 in (18 cm)	
9.84 in (25 cm)	
12.20 in (31 cm)	
3.01 lb(US) (1.367 kg)	
CAR	
4	
15.75 in (40 cm)	
15.75 in (40 cm)	
23.62 in (60 cm)	
14.51 lb(US) (6.58 kg)	
PAM	
100	
86.61 in (220 cm)	
39.37 in (100 cm)	
47.24 in (120 cm)	
392.42 lb(US) (178 kg)	

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	☐ China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	

### Contractual warranty

Warranty	18 month	